

VLS 064 RF AC

ICELINED REFRIGERATOR & ICEPACK FREEZER

This model has a built-in heating element ensuring that the appliance can maintain stable temperatures between +2° to +8°C in all ambient temperatures, setting a new industry standard beyond the PQS requirement.

Watch product video here: ICELINED COMBISERIES



All our VLS AC models are PQS certified according to the newest performance standards. Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.

DIMENSIONS	VALU
Height, mm	95
Width, mm	79
Depth, mm with handle	73
Gross weight, kg	98,3
Net weight, kg	7
SPECIFICATIONS	WALL
	VALU
Gross volume, L	7
Net volume, L Temperature range (43C AMB)	52
	+2 to +8
Hold-over time, hours	4
Energy consumption - stable, kWh/24h Refrigerant	0.6
Freeze protection, grade	R600
Climae class	
WHO PQS code	E003/07
Climate class	E003/0.
Similate Glass	
FEATURES	VALU
Storage baskets, no	
Temperature control	Automat
Lock+keys	YI
Junction box	YI
Adjustable legs	YES, 10c
Safety thermostat	Υ
Appliance plugs	M,G
Industrial grade locking mechanism	Y
Fridge-tag 2E	YI
LOADING QUANTITIES	VALU
Qty. per 20' / 40' container	44/9
VOLTACE DECLII ATION DANCE	
VOLTAGE REGULATION RANGE	VALU
220-240V/50/60Hz	110-278V/50/60
100-127V/50/60Hz	82-159V/50/60I

