

# PRODUCT

## VLS 024 SDD SOLAR DIRECT DRIVEN REFRIGERATOR

The integrated ice bank technology with increased thermal energy storage provides self controlling and reliable temperatures in the area of +2°C to +8°C rated according to highest climate zone within ambient temperature area from +5°C to +43°C.

Solar panels are connected plug & play directly to the appliances.

The junction box further from safeguard the electrical parts, aces services as well as maintenance on the appliance. In addition the appliance now is supplied with an appliance socket.

### SPECIFICATIONS

Gross volume, litres (cu. ft.)	33 (1.16)
Net volume, litres (cu. ft.)	25.5 (0.90)
Temperature range (43°C AMB)	+2° to +8°C
Autonomy, hours	81.7
Refrigerant	R600a
Freeze protection, grade	A
Climate class	T
Min. solar radiation, kWh/m2/day	3.5
Voltage, V Dc	10-45

### FEATURES

Storage baskets, no	1
Temperature control	Automatic
Lock + keys	YES
Plug and Play solar kit	YES
Junction box	YES
Adjustable legs	YES



### WHO SPECIFICATIONS

Test procedure	E003/RF05-VP.3
Performance specification	E003/RF05.3
PQS code	E003/069

### DIMENSIONS

Height, mm (inches)	950 (37.40)
Width, mm (inches)	555 (21.85)
Depth, mm (inches)	645 (25.39)
Gross weight, kg (lbs)	60 (133)
Net weight, kg (lbs)	50 (111)

### LOADING QUANTITIES

Qty. per 20' / 40' container	54 / 114
Qty. per truck (EU standard)	120



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



**COLD CHAIN SOLUTIONS**

**VESTFROST**  
SOLUTIONS

A/S Vestfrost  
Falkevej 12  
DK-6705 Esbjerg Ø  
www.vestfrostolutions.com