

PRODUCT

VLS 504A AC ICELINED REFRIGERATOR

The biggest and most energy efficient icelined refrigerator available today. A sustainable solution constructed with hydrocarbon refrigerant, cyclopentane insulation and recyclable components. Net capacity is increased to 242 Litres due to the specially developed integrated icelining, which is covered with a prepainted aluminium inner liner surface. Reliability and usability is secured through the self-regulating cooling system.

The junction box further from safeguard the electrical parts, aases services as well as maintenance on the appliance. In addition the appliance now is supplied with an appliance socket.



SPECIFICATIONS

Gross volume, litres (cu. ft.)	314 (11.1)
Net volume, litres (cu. ft.)	242 (8.5)
Temperature range (43°C AMB)	+2° to +8°C
Hold-over time, hours	55.27
Energy consumption - stable, kWh/24h	0.64
Energy consumption- cool down, kWh/24h	0.59
Refrigerant	R600a
Freeze protection, grade	A
Climate class	T
Energy supply needed per 24 hours, hours	4

WHO SPECIFICATIONS

Test procedure	E003/RF03-VP3
Performance specification	E003/RF03.4
PQS code	E003/113

FEATURES

Storage baskets, no	10
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES

DIMENSIONS

Height, mm (inches)	905 (35.62)
Width, mm (inches)	1.560 (61.41)
Depth, mm (inches) with handle	700 (27.59)
Gross weight, kg (lbs)	150 (330)
Net weight, kg (lbs)	124 (273)

LOADING QUANTITIES

Qty. per 20' / 40' container	18 / 42
Qty. per truck (EU standard)	

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



COLD CHAIN SOLUTIONS

VESTFROST
SOLUTIONS

A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostolutions.com