

ULTF-C198i

BIOMEDICAL ULT FREEZER

The chest design is an economical choice, that preserves cold well due to the horizontal lid.



CE 01 20 104 738 74



-20°C
-86°C

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DIMENSIONS

Outer Dimensions HxWxD, mm	831x920x608
Inner Dimensions HxWxD, mm	624x760x440
Weight Gross/Net, kg	80 / 63
Material inner cabinet	Painted Steel
Material outer cabinet	Painted Steel
Packaging weight, kg	17
Packaging dimensions HxWxD, mm	900x973x725
Insulation thickness	80
Insulation type	Polyurethane with Cyclopentane
Mobility	Standard: 4 Casters with brakes
Refrigerant, Type / gram	Nature R2 / 90
Variable Speed Compressor	No
Internal Air Distribution	Static
Number of probes	1

CONTROLLER

Controller	i-Care, Touch screen
Controller language	EN, DE, FR
USB Connection	Yes
Logging	Data, Alarms & Events
Temperature graph	Yes
High/Low temp. Alarm	Yes
Open door alarm	No
Probe failure alarm	Yes
Power failure alarm	Yes

STORAGE

Volume, Gross/Net, L	198 / 189
Cryobox "2 capacity	117
2 ml vials capacity	11.700
Inner lids	Yes

FEATURES

Lock	Yes
LED light	No
Battery Backup for Controller, 24h	Yes
VIP (Vacuum Insulated Panel)	No
Door frame heater	No
Porthole	Yes - Ø 12,5 mm
Dry Contact	Yes
Vacuum valve	No
Door	Solid

ULTF-C198i

BIOMEDICAL ULT FREEZER

The chest design is an economical choice, that preserves cold well due to the horizontal lid.



Voltage/Frequency	Voltage/Hz	230V/50Hz
Max Ambient	°C	25°C
Max Humidity	% rh	65%
PERFORMANCE		
All data in RT20°C		
Temperature Range	°C	-20 to -86
Uniformity in performance - difference between top and bottom	°C	+/- 0,9
Pull down time	Minutes	180min to -75°C
Hold over time	Minutes	63 min to -60°C
Noise	dB	55
Energy Saving Mode	kWh/24h	4,839 kWh/24h Set -70
Energy Consumption, kWh / 24h	kWh/24h	5,994 kWh/24h Set -82
Energy year	kWh/year	2187,8 kWh/y Set -82°C
Instant Power Consumption	kW	PD 0,370-0,320/Stable 0,300
Heat Rejection*	W	250
U-Value	W/m ² K	0,2
COOLING COMPONENTS		
Refrigerant/Amount (gram)		Nature R 2/90gr
Number of compressors	pcs	1
Variable speed compressor	Yes/No	No
Internal air distribution (type of)		Static
Evaporator Fan	Yes/No/Variable	No
Condenser Fan	Yes/No/Variable	Yes
Number of probes	pcs	1
Defrost	Yes/No	No

* Heat Rejection is defined as average power based on energy consumption, rounded up to nearest 50W.

ULTF-C198i

BIOMEDICAL ULT FREEZER

The chest design is an economical choice, that preserves cold well due to the horizontal lid.



MODEL	A	B
ULTF-C198i	550	920
ULTF-C296i	890	1260
ULTF-C383i	1190	1560

All measurements in mm.

HB: Height of base
(HB is adjustable when given value is xx-xx)





Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.


ULTF-C198i

BIOMEDICAL ULT FREEZER

The chest design is an economical choice, that preserves cold well due to the horizontal lid.

SENSOR POSITION		MODEL	ULTF-C198i
<p>FRONT VIEW</p> 	<p>TOP VIEW</p> 	<p>Test type</p>	10-point test
		<p>Test environment</p>	Controlled conditions, empty cabinet
		<p>Ambient temperature</p>	20°C
		<p>Humidity</p>	60%
		<p>Set-point</p>	-82°C
		<p>Sensor used</p>	25gr tinned brass formed as a cylinder with a diameter of 15,2 mm
		<p>Installation</p>	Appliance installed according to instruction manual conditions
		<p>Refrigerant</p>	Nature R 2

SENSOR TEMPERATURE										
Sensor position	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10
Max	-81	-81,1	-81,1	-80,7	-79,2	-80,5	-81	-80,4	-80,8	-79,8
Avg.	-81,9	-82,1	-81,9	-81,6	-79,8	-81,1	-81,6	-81,1	-81,6	-80,6
Min.	-83,1	-83,5	-83	-82,9	-80,7	-82	-82,5	-82	-82,6	-81,7



TYPICAL PERFORMANCE IN AMBIENT 20°C – EMPTY CABINET	
Avg. cabinet temperature	-81,3°C
Peak variation from set-point	+/- 1,2°C
Stability in avg.	0,9°C
1 min. door open recovery to -75°C avg. temperature	<1 min.
Cycle rate on/off	35 / 6 min.
Duty cycle	81,6%
Energy consumption - Normal mode	5,99 kWh/day
Energy consumption - Energy saving mode	4,83 kWh/day
Pull down time to -75°C avg. temperature	180 min.
Hold over time from -82°C to -60°C	63 min.
Heat rejection	375 W

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.