

VLS 354A AC ICELINED REFRIGERATOR

The icelined refrigerator series has a built-in heating element ensuring that the appliance can maintain stable temperatures between +2° to +8°C in all ambient temperatures, setting a new industry standard beyond the PQS requirement.

Watch product video here: ICELINED REFRIGERATOR SERIES



All our VLS AC models are PQS certified according to the newest performance standards. Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.

DIMENSIONS	VALUE
Height, mm	910
Width, mm	1120
Depth, mm with handle	700
Gross weight, kg	148
Net weight, kg	118
SPECIFICATIONS	VALUE
Gross volume, L	209
Net volume, L	127
Temperature range (43C AMB)	+2 to +8C
Hold-over time, hours	54.7
Energy consumption - stable, kWh/24h	0.62
Energy consumption - cool down, kWh/24h	0.64
Refrigerant	R600a
Freeze protection, grade	A
Climae class	Т
WHO PQS code	E003/111
FEATURES	VALUE
Storage baskets, no	7
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
Appliance plugs	M,G,F
Industrial grade locking mechanism	YES
LOADING QUANTITIES	VALUE
Qty. per 20' / 40/ container	26 / 60
VOLTAGE REGULATION RANGE	VALUE
220-240V/50/60Hz	110-278V/50/60Hz
100-127V/50/60Hz	



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.