VT75

CONSTRUCTION

PACKAGING
Dimensions HxWxD, mm

Weight, Gross, kg

Ambient temperature, °C

Temperature range, °C
COOLING SYSTEM
Refrigerant, type

Refrigerant amount, gr Static/ventilated

ELECTRICAL Voltage, V

Frequency, Hz Voltage 110/60, V-Hz

ENERGY

Energy class EEI

FEATURES
Cabinet color

Alternative lid

Castors/feet

Insulation, mm

OPTION
Graphics

Baskets SHIPPING

Input power, watt

Inside material/color

Door or lid color/type

Defrost & removal of water

Quantity in standard truck

Quantity in 20 ft container
Quantity in 40 ft HC container

Type of thermometer

Porthole for sensor, ø12 mm

Energy consumption, kWh/24h

Energy consumption, kWh/year

Potential free contact for remote control

Type of thermostat

Weight, Net, kg

BASKETS
No. of baskets, pcs
TEMPERATURE

Climate class

VOLUME Volume, Gross, L Volume, Net, L WEIGHT

Outer Dimensions, HxWxD, mm

Inner Dimensions, HxWxD, mm

LOW TEMPERATURE CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.



-40°C

870x555x555

465x390x390

48

42

+10 to +30

-40 to -60

Mix of hydrocarbons

Static

220-240 50

Option

Yes

Yes

22

415

White

n/a Yes

Feet

80

Manual

Option

288

114

Electronic

Electronic

not needed

not needed

White, lift up

White painted steel

_
Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

A/S Vestfrost | Falkevej 12 | DK-6705 Esbjerg Ø | www.vestfrostsolutions.com VESTFR **ST **SOLUTIONS**