PRODUCT

VLS 504A AC

ICELINED REFRIGERATOR

This sustainable model constructed with recyclable components, has a built-in heating element ensuring that the appliance can maintain stable temperatures between +2°to +8°C in all ambient temperatures, setting a new industry standard beyond the PQS requirement. It has an Integrated and extended voltage stabilizer as standard in line with PQS E007/VS01-VP.5 and is supplied with M, G, F and B appliance plugs. All our VLS AC models are PQS certified according to the newest performance standards. Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.



Gross volume, L	314
Net volume, L	242
Temperature range (43C AMB)	+2 to +8C
Hold-over time, hours	55.3
Energy consumption - stable, kWh/24h	0.64
Energy consumption - cool down, kWh/24h	N/A
Refrigerant	R600a
Freeze protection, grade	А
Climae class	T
WHO PQS code	E003/113



Storage baskets, no	7
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
Appliance plugs	M,G,F
Industrial grade locking mechanism	YES



DIMENSIONS

Height, mm	910
Width, mm	1560
Depth, mm with handle	700
Gross weight, kg	194
Net weight, kg	172

LOADING QUANTITIES

Qty. per 20' / 40' container	18 / 42

VOLTAGE REGULATION RANGE

220-240V/50/60Hz	110-278V/50/60Hz
100-127V/50/60Hz	82-159V/50/60Hz





Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

