

PRODUCT

VLS 024A SDD

SOLAR DIRECT DRIVEN VACCINE REFRIGERATOR

The appliance can maintain stable temperatures between +2°C to +8°C in all ambient temperatures. The included solar panel kit of 2 x 180W, is connected plug & play, directly to the appliance. The VLS SDD has an integrated safety thermostat, and junction box to safeguard and provide easy access to electrical components. The appliance comes with industrial locking mechanism, adjustable legs and storage baskets. All VLS SDD are PQS certified according to the newest performance standards.

Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.

SPECIFICATIONS

Gross volume, L	33
Net volume, L	25,5
Temperature range (43C AMB)	+2 to +8C
Autonomy, hours	82
Energy consumption - stable, kWh/24h	0.25
Energy consumption - cool down, kWh/24h	0.25
Refrigerant	R600a
Freeze protection, grade	A
Climae class	T
WHO PQS code	E003/069

FEATURES

Storage baskets, no	1
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
Appliance plugs	M,G,F
Industrial grade locking mechanism	YES




DIMENSIONS

Height, mm	950
Width, mm	550
Depth, mm with handle	650
Gross weight, kg	75
Net weight, kg	49

LOADING QUANTITIES

Qty. per 20' / 40' container	44 / 92
------------------------------	---------

*excl. solar panels



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



COLD CHAIN SOLUTIONS

VESTFROST
SOLUTIONS

A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostsolutions.com