VLS 096A RF SDD

SOLAR DIRECT DRIVEN TRUE COMBI he True Combi series can maintain stable temperatures between +2°to +8°C in all ambient temperatures. he included solar panel kit of 4 x 180W, is connected plug & blay, directly to the appliance.		
Natch product video here: TRUE COMBI SERIES		
DIMENSIONS		
Height, mm	92	
Width, mm	151	
Depth, mm with handle	75	
Gross weight, kg (incl. packaging)	19	
Net weight, kg	15	
Packed dimensions HxWxD, mm	1065x1560x78	
Shipping volume m3	1,	
REFRIGERATOR SPECIFICATIONS		
Gross volume, L	14	
Net volume, L	ון	
Temperature range (+43°C AMB)	+2°C to +8°	
Autonomy, hours (+43°C AMB)	114,3	
Refrigerant	R600	
Freeze protection, grade		
Climate class		
WHO PQS code	E003/13	
FREEZER SPECIFICATIONS		
Gross volume, L	5	
Water pack storage capacity, L	28 x 0.	
Water pack freezing capacity, kg/24h	2	
Temperature range (+43°C AMB)	-15° to -25°	
Refrigerant	R290 + R600	
FEATURES		
Storage baskets, no		
Temperature control	Automati	
Lock + keys	YE	
Junction box	YE	
Adjustable legs	YES, 10cr	
Safety thermostat	YE	
Charging port	USB A 5	
EMS level 3 as an option	YE	
Industrial grade locking mechanism	YE	
Automatic drainage system	YE	
LOADING QUANTITIES		
Qty. per 20' / 40' container	14 / 3	

All VLS SDD RF models have been tested and PQS approved according to the newest performance standards. This model comes equipped with our fully integrated remote equipment monitoring system (EMS) as standard. An upgrade to EMS level 3 is available as an option for enhanced monitoring capabilities.

WHO PQS (Performance, Quality, and Safety) ensures that immunization equipment meets international standards. This certification guarantees quality, reliability, and safety. Non-PQS certified equipment risks poor performance, safety issues, and higher costs.

: *