The MF series provides vaccine storage and icepack freezing with stable temperature control in the range -15°C to -25°C. The units' thick insulation ensures exceptional hold-over time in case of power cut.



Unight man	910
Height, mm	72:
Weight, mm	
Depth, mm with handle	70
Gross weight, kg (incl. packaging)	69,91
Net weight, kg	62,
Packed dimensions HxWxD, mm	1025x785x72 0.5i
Shipping volume m3	0,56
SPECIFICATIONS	
Gross volume, L	10
Icepack freezing capacity, kg/24h	7;
Icepack storage capacity, pcs	64 x 0,6
Temperature range (+43°C AMB)	-15° to -25°C
Hold-over time, hours (+43°C AMB)	2,4
Energy consumption - stable, kWh/24h	2,2
Energy consumption - cool down, kWh/24h	2,4
Refrigerant	R600
WHO PQS code	E003/02
Climate class	
FEATURES	
Storage baskets, no	
Temperature control	Automati
Lock + keys	YE
Adjustable legs	YES, 10 cn
Junction box	YE
Safety thermostat	No
Appliance plugs	E, F, (
Industrial grade locking mechanism	YE
Fridge-tag 2E	YE
LOADING QUANTITIES	
Qty. per 20' / 40/ container	44/9
Qty. per truck (EU standard)	10
VOLTAGE REGULATION RANGE	
220-240V/50/60Hz	110-278V/50/60H
100-127V/50/60Hz	82-159V/50/60H

All MF AC models are PQS certified according to the newest performance standards.

WHO PQS (Performance, Quality, and Safety) ensures that immunization equipment meets international standards. This certification guarantees quality, reliability, and safety. Non-PQS certified equipment risks poor performance, safety issues, and higher costs.