The MF series provides vaccine storage and icepack freezing with stable temperature control in the range –15°C to –25°C. The units' thick insulation ensures exceptional hold-over time in case of power cut.

Watch product video here: MF SERIES



DIMENSIONS	T
Height, mm	910
Weight, mm	720
Depth, mm with handle	700
Gross weight, kg (incl. packaging)	69,90
Net weight, kg	62,2
Packed dimensions HxWxD, mm	1025x785x727
Shipping volume m3	0,58
SPECIFICATIONS	
Gross volume, L	105
Icepack freezing capacity, kg/24h	7,2
Icepack storage capacity, pcs	64 x 0,6 l
Temperature range (+43°C AMB)	-15° to -25°C
Hold-over time, hours (+43°C AMB)	2,8
Energy consumption - stable, kWh/24h	2,24
Energy consumption - cool down, kWh/24h	2,4
Refrigerant	R600c
WHO PQS code	E003/024
Climate class	Т
FEATURES	
Storage baskets, no	2
Temperature control	Automatic
Lock + keys	YES
Adjustable legs	YES, 10 cm
Junction box	YES
Safety thermostat	NC
Appliance plugs	E, F, G
Industrial grade locking mechanism	YES
Fridge-tag 2E	YES
LOADING QUANTITIES	
Qty. per 20' / 40/ container	44 / 92
Qty. per truck (EU standard)	108
VOLTAGE REGULATION RANGE	
220-240V/50/60Hz	110-278V/50/60Hz
100-127V/50/60Hz	82-159V/50/60Hz
Integrated and extended voltage stabilizer as standard in line wit	

All MF AC models are PQS certified according to the newest performance standards.

WHO PQS (Performance, Quality, and Safety) ensures that immunization equipment meets international standards. This certification guarantees quality, reliability, and safety. Non-PQS certified equipment risks poor performance, safety issues, and higher costs.