

PRODUCT

VLS 304A AC ICELINED REFRIGERATOR

This sustainable model constructed with recyclable components, has a built-in heating element ensuring that the appliance can maintain stable temperatures between +2°to +8°C in all ambient temperatures, setting a new industry standard beyond the PQS requirement. It has an Integrated and extended voltage stabilizer as standard in line with PQS E007/VS01-VP.5 and is supplied with M, G, F and B appliance plugs. All our VLS AC models are PQS certified according to the newest performance standards. Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.

SPECIFICATIONS

Gross volume, L	157
Net volume, L	98
Temperature range (43C AMB)	+2 to +8C
Hold-over time, hours	55.5
Energy consumption - stable, kWh/24h	0.60
Energy consumption - cool down, kWh/24h	0.69
Refrigerant	R600a
Freeze protection, grade	A
Climae class	T
WHO PQS code	E003/110

FEATURES

Storage baskets, no	4
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
Appliance plugs	M,G,F
Industrial grade locking mechanism	YES



DIMENSIONS

Height, mm	910
Width, mm	920
Depth, mm with handle	700
Gross weight, kg	132,20
Net weight, kg	104,80

LOADING QUANTITIES

Qty. per 20' / 40' container	36 / 72
------------------------------	---------

VOLTAGE REGULATION RANGE

220-240V/50/60Hz	110-278V/50/60Hz
100-127V/50/60Hz	82-159V/50/60Hz



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



COLD CHAIN SOLUTIONS

VESTFROST
SOLUTIONS

A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostsolutions.com