

# PRODUCT

## VLS 094A SDD

### SOLAR DIRECT DRIVEN VACCINE REFRIGERATOR

The appliance can maintain stable temperatures between +2°to +8°C in all ambient temperatures. The included solar panel kit of 2 x 180W, is connected plug & play, directly to the appliance. The VLS SDD has an integrated safety thermostat, and junction box to safeguard and provide easy access to electrical components. The appliance comes with industrial locking mechanism, adjustable legs and storage baskets. All VLS SDD are PQS certified according to the newest performance standards.

Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.



## SPECIFICATIONS

Gross volume, L	151
Net volume, L	92
Temperature range (43C AMB)	+2 to +8C
Autonomy, hours	72,5
Refrigerant	R600a
Freeze protection, grade	A
Climae class	T
WHO PQS code	E003/107

## FEATURES

Storage baskets, no	1
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
Industrial grade locking mechanism	YES


## DIMENSIONS

Height, mm	910
Width, mm	920
Depth, mm with handle	700
Gross weight, kg	128
Net weight, kg	107

## LOADING QUANTITIES

Qty. per 20' / 40' container	22/48
------------------------------	-------

\*excl. solar panels



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



**COLD CHAIN SOLUTIONS**

# VESTFROST

**SOLUTIONS**

A/S Vestfrost  
Falkevej 12  
DK-6705 Esbjerg Ø  
[www.vestfrostolutions.com](http://www.vestfrostolutions.com)