


MS185

UPRIGHT DISPLAY COOLER SOLID DOOR

Experience the Low EC technology that ensures optimal energy consumption, paired with our Vestfrost door design for consistent temperature maintenance. The easy clean plastic inner liner simplifies maintenance, while the internal fan guarantees uniform cooling.



DIMENSIONS	
Outer dimensions, HxWxD, mm	1795x595x600
PACKAGING	
Dimensions HxWxD, mm	1935x640x615
VOLUME	
Volume, Gross, L	373
Volume, Net, L	358
Capacity 0,33 L cans	476
Capacity 0,5 L bottles	406
WEIGHT	
Weight, Gross, kg	80
Weight, Net, kg	71
SHELVES	
No. of shelves, pcs	5
Max. load, kg	25
Shelf material	White wire
COOLING SYSTEM	
Refrigerant	R600a
Climate class	3
Temperature range, °C	+1 to +9
Type of thermostat	Electronical
Static/Ventilated	Ventilated
ELECTRICAL	
Voltage, V	220-240
Frequency, Hz	50
Electronic display	Yes
ENERGY	
Energy consumption, kWh/24h	0,871
Energy consumption, kWh/year	318
Energy class	B
EEL	19,5
FEATURES	
Light inside top	Yes
Light in door side	No
Cabinet color (All PS)	White
Inside color	White PS
Door color/type	White, solid
Lock	No
Wheels	No
Defrost & removal of water	Automatic
Noise	<45
Insulation, mm	45
Side change of door possible	Yes
Possible to build in	No
SHIPPING	
Quantity in standard truck	180
Quantity in 20 ft container	27
Quantity in 40 ft HC container	162

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.