

PRODUCT

VLS 096A RF SDD SOLAR DIRECT DRIVEN COMBI

The appliance can maintain stable temperatures between +2°C to +8°C in all ambient temperatures. The included solar panel kit of 4 x 180W, is connected plug & play, directly to the appliance. The VLS SDD has an integrated safety thermostat, and junction box to safeguard and provide easy access to electrical components. The appliance comes with industrial locking mechanism, adjustable legs and storage baskets. All VLS SDD RF models have been tested and PQS approved according to the newest performance standards. Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.




REFRIGERATOR SPECIFICATIONS

Gross volume, L	147
Net volume, L	110
Temperature range (43C AMB)	+2 to +8C
Autonomy, hours	114
Refrigerant	R600a
Freeze protection, grade	A
Climae class	T
WHO PQS code	E003/132

FEATURES

Storage baskets, no	2
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
EMS as option	YES
Industrial grade locking mechanism	YES
Automatic drainage system	YES



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



COLD CHAIN SOLUTIONS

FREEZER SPECIFICATIONS

Gross volume, L	
Water pack storage capacity, L	28 x 0.6
Water pack freezing capacity, L	2.4
Temperature range (43C AMB)	-18 to -28C
Refrigerant	R290 + R600a

DIMENSIONS

Height, mm	940
Width, mm	1510
Depth, mm with handle	750
Gross weight, kg	190
Net weight, kg	150

VESTFROST
SOLUTIONS

A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostolutions.com