## VLS 026 RF SDD

## **SOLAR DIRECT DRIVEN COMBI**

Built-in heating element ensuring that the appliance can maintain stable  $\pm 2^{\circ}\text{to} \pm 8^{\circ}\text{C}$  in all ambient temperatures, setting a new industry standard beyond the PQS requirement. The included solar panel kit of 4 x 180W, is connected plug & play, directly to the appliance.

Watch product video here: SOLAR COMBISERIES



+2°C

DIMENSIONS	u u
Height, mm	950
Width, mm	m
Depth, mm with handle	650
Gross weight, kg (incl. packaging)	14
Net weight, kg	no
Packed dimensions HxWxD, mm	1065 x 1168 x 67
Shipping volume m3	0,8
SPECIFICATIONS	
Gross volume, L	3:
Net volume, L	20
Temperature range (+43°C AMB)	+2°C to +8°C
Autonomy, hours (+43°C AMB)	73;
Refrigerant	R600c
Freeze protection, grade	,
Climate class	
WHO PQS code	E003/09
FREEZER SPECIFICATIONS	
Gross volume, L	34,
Water pack storage capacity, L	29 x 0.
Water pack freezing capacity, kg/24h	1.
Temperature range (+43°C AMB)	-15° to -25°C
Refrigerant	R290 + R6000
FEATURES	
Storage baskets, no	
Temperature control	Automati
Lock+keys	YE
Junction box	YE
Adjustable legs	YES, 10cn
Safety thermostat	YE
Charging port	USB A 5
Industrial grade locking mechanism	YE
EMS level 3 as an option	YE
LOADING QUANTITIES	
Qty. per 20' / 40' container	13 / 30
*incl. solar panels - see our solar panel datasheet	

All VLS SDD RF models have been tested and PQS approved according to the newest performance standards. This model comes equipped with our fully integrated remote equipment monitoring system (EMS) as standard. An upgrade to EMS level 3 is available as an option for enhanced monitoring capabilities.

WHO PQS (Performance, Quality, and Safety) ensures that immunization equipment meets international standards. This certification guarantees quality, reliability, and safety. Non-PQS certified equipment risks poor performance, safety issues, and higher costs.

Updated 05/2025