## **VLS 504A AC**

## **ICELINED REFRIGERATOR**

The icelined refrigerator series has a built-in heating element ensuring that the applicance can maintain stable temperatures between +2° to +8°C in all ambient temperatures, setting a new industry standard beyond the PQS requirement.

Watch product video here: ICELINED REFRIGERATOR SERIES

the state of the s

DIMENSIONS	1
Height, mm	910
Width, mm	156
Depth, mm with handle	70
Gross weight, kg (incl. packaging)	193,
Net weight, kg	17:
Packed dimensions HxWxD, mm	1025x1620x72
Shipping volume m3	1,2
SPECIFICATIONS	
Gross volume, L	31.
Net volume, L	24.
Temperature range (+43°C AMB)	+2°C to +8°C
Hold-over time, hours (+43°C AMB)	55.2
Energy consumption - stable, kWh/24h	0.6
Refrigerant	R600d
Freeze protection, grade	
Climate class	
WHO PQS code	E003/11:
FEATURES	
Storage baskets, no. top	
Storage baskets, no. bottom	
Temperature control	Automati
Lock + keys	YE
Junction box	YE
Adjustable legs	YES, 10cn
Safety thermostat	YE
Appliance plugs	E, F, (
Industrial grade locking mechanism	YE
EMS level 3 as an option	YE
LOADING QUANTITIES	
Qty. per 20' / 40/ container	18 / 4
VOLTAGE REGULATION RANGE	
220-240V/50/60Hz	110-278V/50/60Н
100-127V/50/60Hz	
	82-159V/50/60H

All our VLS AC models are PQS certified according to the newest performance standards. This model comes equipped with our fully integrated remote equipment monitoring system (EMS) as standard. An upgrade to EMS level 3 is available as an option for enhanced monitoring capabilities.

WHO PQS (Performance, Quality, and Safety) ensures that immunization equipment meets international standards. This certification guarantees quality, reliability, and safety. Non-PQS certified equipment risks poor performance, safety issues, and higher costs.