

ULTF-37i

ULT TECHNICAL SPECIFICATIONS



-20°C
-86°C

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DIMENSIONS

Outer Dimensions HxWxD, mm	631x630x675
Depth incl. door handle	745
Inner Dimensions HxWxD, mm	433x439x271
Weight Gross/Net, kg	70 / 59
Material inner cabinet	Stainless steel
Material outer cabinet	Painted Steel
Packaging weight, kg	11
Packaging dimensions HxWxD, mm	850x800x850
Insulation thickness	80
Insulation type	Polyurethane with Cyclopentane
Mobility	Standard: Adjustable Feet / Option: Castors
Refrigerant, Type / gram	Nature R 2/96gr

FEATURES

Lock	☒
LED light	☒
Battery Backup for Controller, 24h	☒
Porthole	☒
Porthole size	20 mm
Dry contact	☒
Door reversibility	☐
Vacuum valve	☒
VIP (Vacuum Insulated Panel)	☒

STORAGE

Capacity (L)	37
--------------	----

ALARMS

High / Low temperature	☒
Open door	☒
Power failure	☒
Probe failure	☒

COOLING

Refrigerant	Nature R / 96
Noise	< 48
Voltage	230 V
Frequency	50 Hz
Temperature range	-20 / -86

ULTF-37i

ULT TECHNICAL SPECIFICATIONS




Voltage/Frequency	Voltage/Hz	230 V, 50 Hz
Max Ambient	°C	32
Max Humidity	% rh	65
PERFORMANCE		
All data in RT20°C		
Temperature Range	°C	-20 to -86
Uniformity in performance - difference between top and bottom	°C	+/- 2,5
Pull down time	Minutes	84 min. to -75°C
Hold over time	Minutes	N/A
Noise	dB	< 48
Energy Consumption, kWh / 24h	kWh/24h	2,94 kWh/24h Set -80
Energy year	kWh/year	1186,6kWh/y Set -82°C
Instant Power Consumption	kW	PD 0,300/Stable 0,190
Heat Rejection*	W	150
U-Value	W/m ² K	N/A
COOLING COMPONENTS		
Refrigerant/Amount (gram)		Nature R 2/96gr
Number of compressors	pcs	1
Variable speed compressor	Yes/No	Yes
Internal air distribution (type of)		Static
Evaporator Fan	Yes/No/Variable	No
Condenser Fan	Yes/No/Variable	Yes
Number of probes	pcs	2
Defrost	Yes/No	No
CONTROLLER		
Controller	y/n/optional	yes
Controller type		i-Care touch
USB Connection	y/n	yes
Data connection	USB	yes
Controller abilities		logging of data & alarms
Controller languages		EN, DE, FR
Temperature curve in controller	y/n	yes

* Heat Rejection is defined as average power based on energy consumption, rounded up to nearest 50W.

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

ULTF-37i

ULT TECHNICAL SPECIFICATIONS





DIMENSIONS

Height, mm	631
Width, mm	630
Depth, mm	675
Depth incl. handle, mm	745

All measurements in mm.



HB: Height of base
(HB is adjustable when given value is xx-xx)




Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

ULTF-37i

ULT TECHNICAL SPECIFICATIONS

SENSOR POSITION		MODEL	ULTF-37i
FRONT VIEW  TOP VIEW 		Test type	8-point test
		Test environment	Controlled conditions, empty cabinet
		Ambient temperature	20°C
		Humidity	60%
		Set-point	-82°C
		Sensor used	25gr tinned brass formed as a cylinder with a diameter of 15,2 mm
		Installation	Appliance installed according to instruction manual conditions
		Refrigerant	Nature R

SENSOR TEMPERATURE								
Sensor position	P1	P2	P3	P4	P5	P6	P7	P8
Max	-79,7	-80,2	-80,1	-79,9	-80	-83,1	-83,1	-84,6
Avg.	-80	-80,5	-80,4	-80,2	-80,3	-83,5	-83,6	-85
Min.	-80,4	-81	-80,8	-80,5	-80,7	-84,1	-84,1	-85,4



TYPICAL PERFORMANCE IN AMBIENT 20°C – EMPTY CABINET	
Avg. cabinet temperature	-81,7°C
Peak variation from set-point	+/- 2,5°C
Stability in avg.	0,5°C
1 min. door open recovery to -75°C avg. temperature	20 min.
Cycle rate on/off	25,7 / 6,7 min.
Duty cycle	78,7%
Energy consumption – Normal mode	3,25 kWh/day
Energy consumption – Energy saving mode	2,92 kWh/day
Pull down time to -75°C avg. temperature	84 min.
Hold over time from -82°C to -60°C	105 min.
Heat rejection	306 W

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.