**DIMENSIONS** 

The icelined refrigerator series has a built-in heating element ensuring that the applicance can maintain stable temperatures between +2° to +8°C in all ambient temperatures, setting a new industry standard beyond the PQS requirement.

Watch product video here: ICELINED REFRIGERATOR SERIES



910	
260	
700 159	
27,2	
727	
),98	
235	
145 3°C	
3°C	
55	
55 ).67	
)()a	
А	
Т	
/112	
4	
3	
atic	
YES	
YES	
cm	
YES	
F, G	
YES	
YES	
50	
0Hz	
0Hz	

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice

910
1260
700
159
127,2
1025x 1320x727
0,98
235
145
+2°C to +8°C
55
0.67
R600a
А
Т
E003/112
4
3
Automatic
YES
YES
YES, 10cm
YES
E, F, G
YES
YES
24/50
110-278V/50/60Hz

All our VLS AC models are PQS certified according to the newest performance standards. This model comes equipped with our fully integrated remote equipment monitoring system (EMS) as standard. An upgrade to EMS level 3 is available as an option for enhanced monitoring capabilities.

WHO PQS (Performance, Quality, and Safety) ensures that immunization equipment meets international standards. This certification guarantees quality, reliability, and safety. Non-PQS certified equipment risks poor performance, safety issues, and higher costs.