VT 147

LOW TEMPERATURE CHEST FREEZER

The VT low temperature freezers creates the possibility to maintain temperatures as low as -60°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution.

-40°C
-60°c

CONSTRUCTION	
Outer Dimensions, WxDxH, mm	725x605x885
Inner Dimensions, WxDxH, mm	560x440x635
PACKAGING	
Dimensions WxDxH, mm	-
VOLUME	
Volume, Gross/Net, L	140/133
WEIGHT	
Weight, Gross/Net, kg	54,6/50,7
BASKETS	
No. of baskets, pcs	1
TEMPERATURE	
Ambient temperature, °C	+10 to +30
Climate class	-
Temperature range, °C	-40 to -60
COOLING SYSTEM	
Refrigerant, type	Mix of hydrocarbons
Refrigerant amount, gr	-
Static/ventilated	Static
ELECTRICAL	
Voltage, V	220-240
Frequency, Hz	50
Voltage 110/60, V-Hz	Option
Variable speed compressor	option
Type of controller	Dixell XR30CX
Potential free contact for remote control	Yes
Porthole for sensor , ø12 mm	Yes
ENERGY	
Energy consumption, kWh/24h	3,707
Energy cons. 24 h variable speed	2,29
Input power, watt	415
FEATURES	
Cabinet color	White
Inside material/color	White painted steel
Door or lid color/type	White, lift up
Alternative lid	n/a
Lock	Yes
Castors/feet	Castors
Defrost & removal of water	Manual
Insulation, mm	80
OPTION	
Controller language	3 digits
USB connection	No
Logging	No
Temperature graph	No
High / low temp. alarm	Yes
Probe failure alarm	Yes
Power failure alarm	No
SHIPPING	
Quantity in standard truck	216
Quantity in 20 ft container	-
Quantity in 40 ft HC container	94

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

A/S Vestfrost | Falkevej 12 | DK-6705 Esbjerg Ø | www.vestfrostsolutions.com

VESTFROST SOLUTIONS