R-350 ESSENTIAL

GREAT CAPACITY AND LOW POWER CONSUMPTION

ECO MODE AVAILABLE

A built-in ECO function together with the optimized cooling system and hydrocarbon refrigerants save energy and reduces your carbon footprint. Integrated LED light in the door frame offers full exposure of the stored contents while still maintaning a low operational cost. The flexible and robust glass shelves can easily be adjusted to fit your products.



+2°C
+10°C

DIMENSIONS	
Outer Dimensions HxWxD, mm	1860x595x595
Inner Dimensions HxWxD, mm	1550x500x415
Weight Gross/Net, kg	81 / 79
Material inner cabinet	White/PS
Material outer cabinet	Painted steel
Packaging weight, kg	2
Packaging dimensions HxWxD, mm	1925x636x671
Insulation thickness	42
Insulation type	Polyurethane with cyclopentane
Mobility	2 feet front, 2 wheels back
Refrigerant, Type / gram	R600a / 50g
CONTROLLER	
Controller	Danfoss
Controller language	No Language - only 3 digits
USB Connection	No
Logging	No
Temperature graph	No
High/Low temp. Alarm	Visual
Open door alarm	Visual
Probe failure alarm	Visual
STORAGE	
Volume, Gross/Net, L	350 / 255
SPOR Full length half length	21 Full / 2 Half
Shelves Full length half length	5 Full / 1 Half
Max. shelf load, kg	20 / 11
Shelf type	Perforated stainless steel
FEATURES	
Lock	Yes
Defrost tray	No
Lid color/type	Glass
Light inside lid	Yes
Cabinet color	White
Inside color/material	White / PS
Electronic display	Yes

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

Updated 10/2026

A/S Vestfrost | Falkevej 12 | DK-6705 Esbjerg Ø | www.vestfrostsolutions.com

VESTFROST SOLUTIONS

R-350 ESSENTIAL

GREAT CAPACITY AND LOW POWER CONSUMPTION

ECO MODE AVAILABLE

Voltage/Frequency	Voltage/Hz	230V/50Hz
Max Ambient	°C	32°C
Max Humidity	% rh	65%
PERFORMANCE		
All data in RT20°C		
Temperature Range	°C	2 to 10
Uniformity in performance - difference between top and bottom	°C	+/- 0,8
Pull down time	Minutes	27 min to 6°C
Hold over time	Minutes	69 min to 10°C
Noise	dB	45
Energy Consumption, kWh / 24h	kWh/24h	0,962kWh/24h set 5°C
Energy year	kWh/year	351kWh/y set 5°C
Energy class		B
Instant Power Consumption	kW	PD 0,18 /Stable 0,16
Heat Rejection*	W	50
U-Value	W/m^2 K	-
COOLING COMPONENTS		
Refrigerant/Amount (gram)		R600a/50gr
Number of compressors	pcs	1
Variable speed compressor	Yes/No	No
Internal air distribution (type of)		Dual Air Stream
Evaporator Fan	Yes/No/Variable	Yes
Condenser Fan	Yes/No/Variable	No
Number of probes	pcs	2
Defrost	Yes/No	Yes - automatic
FEATURES		
Safety thermostat	y/n/optional	No
Lock	y/n	Yes
LED light	y/n	Yes
Battery Back Up For Controller	y/n/optional	No
Porthole	y/n - Ømm	Yes - Ø 12,7 mm
Dry contact	y/n	No
Door	glass/solid	Glass
Reference bottle	y/n/optional	No
Door closure	y/n/optional	Yes
Door reversibility	y/n	Yes
Automatic Hold 90°C	y/n	No
Vacuum valve	y/n	No
Vacuum Insulation Panels (VIP)	y/n	No
Bluetooth connection	y/n	Yes

* Heat Rejection is defined as average power based on energy consumption, rounded up to nearest 50W.

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

Updated 10/2026


A/S Vestfrost | Falkevej 12 | DK-6705 Esbjerg Ø | www.vestfrostsolutions.com

VESTFROST SOLUTIONS

R-350 ESSENTIAL

GREAT CAPACITY AND LOW POWER CONSUMPTION


ECO MODE AVAILABLE



DIMENSIONS

Height, mm	1860
Width, mm	600
Depth, mm	595
Incl. handle, mm	640
Incl. open door, mm	1180

All measurements in mm.



Mobility: 2 feet front, 2 wheels back

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.


R-350 ESSENTIAL

GREAT CAPACITY AND LOW POWER CONSUMPTION


ECO MODE AVAILABLE

SENSOR POSITION

FRONT VIEW



TOP VIEW




MODEL	R-350 ESSENTIAL
Test environment	Controlled conditions,
Sensor used	25gr tinned brass formed as a cylinder with a diameter of 15,2 mm
Installation	Appliance installed according to instruction manual conditions
Refrigerant	R600a


SENSOR TEMPERATURE WITH SET POINT 5°C IN STABLE CONDITION 24HR AMBIENT 20°C

Sensor position	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15
Max	4,1	4	4,5	4,6	4,2	3,2	3,2	3,7	4,1	3,5	4,6	3,5	3,9	4	3,8
Avg.	5,5	5,4	5,3	5,8	5,5	4,9	5,2	5,2	5,5	5,1	5,3	5	5,3	5	4,8
Min.	3	2,9	3,8	3,8	3,3	2	1,6	2,5	3,1	2,5	4,1	2,5	2,8	3,4	3,1

WARM UP & PULL DOWN



CYCLIC OPERATION



TYPICAL PERFORMANCE IN AMBIENT 20°C - EMPTY CABINET

Avg. cabinet temperature at 5°C setpoint	3,9°C
Uniformity	+/- 1,4°C
Stability	2,2°C
1 min. door open recovery to 6°c	6 min.
Cycle rate on/off	7 / 22 min.
Duty cycle	23%
Energy consumption	0,962 kWh/day
Pull down time to 6°C	27 min.
Hold over time from avg to 10°C	69 min.
Heat rejection	- W
U-Value	- W/m^2*K
Noise	45 dB

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

A/S Vestfrost | Falkevej 12 | DK-6705 Esbjerg Ø | www.vestfrostsolutions.com

VESTFROST SOLUTIONS