

PRODUCT OVERVIEW

FOOD SOLUTIONS





VESTFROST FOOD

PROFESSIONAL COOLING SOLUTIONS

Designed to ensure optimal preservation and presentation,
maintaining the perfect temperature to guarantee freshness and flavor.

Cooling with confidence

CONTENT


VESTFROST SOLUTIONS – FOOD

DISPLAY COOLERS +1°C TO +18°C	2-7
STORAGE COOLERS +4°C TO +12°C	8-9
WINE CABINETS +5°C TO +22°C	10-13
DISPLAY FREEZERS -16°C TO -24°C	14-15
STORAGE FREEZERS -16°C TO -25°C	16-21
LOW TEMP. CHEST FREEZERS -10°C TO -45°C	22-23
LOW TEMP. CHEST FREEZERS -40°C TO -60°C	24-25

CHILLING PRECISION

DISPLAY COOLERS

UPRIGHT



M85



M95



M130



M150



M180



M185

DISPLAY COOLERS




DIMENSIONS	M85	M95	M130	M150	M180	M185
Outer dimensions, HxWxD, mm	841x493x588	821x595x572	1265x470x545	1560x600x595	1860x600x595	1795x600x595
PACKAGING						
Dimensions, HxWxD, mm	880x550x650	880x655x660	1365x500x570	1625x636x671	1925x671x636	1935x640x615
VOLUME						
Volume, Gross, L	138	164	189	281	350	373
Volume, Net, L	124	146	179	193	255	358
Capacity 0,33 L cans	140	140	192	343	441	476
Capacity 0,5 L bottles	-	-	-	189	231	406
WEIGHT						
Weight, Gross, kg	39	49	45	73	81	49
Weight, Net, kg	35	44	42	71	79	44
SHELVES						
No. of shelves, pcs	2+1	3	3	4+1	5+1	5
Max. load, kg	25	29	25	25	25	35
Shelf material	Black wire	Black wire	White wire	White wire	White wire	Wire w PE
COOLING SYSTEM						
Refrigerant	R600a	R600a	R600a	R600a	R600a	R600a
Climate class	3	3	3	3	3	3
Temperature range, °C	+2 to +10	+2 to +10	+1 to +9	+2 to +10	+1 to +7	+1 to +9
Type of thermostat	Electronic	Electronic	Mechanical	Electronic	Electronic	Mechanical
Static/Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
ELECTRICAL						
Voltage, V	220-240	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50	50
Electronic display	Yes	Yes	No	Yes	Yes	No
ENERGY						
Energy consumption, kWh/24h	0,498	0,489	1,134	2,047	2,381	1,55
Energy consumption, kWh/year	182	178	414	747	869	566
Energy class	B	B	C	B	B	C
EEL	17,5	16,1	34,5	13	15	35
FEATURES						
Light inside top	Yes	Yes	No	No	No	No
Light in door side	No	No	Yes	Yes	Yes	Yes
Cabinet color (All PS)	Black	Black	White	White	White or black	White
Inside color	Black PS	Black PS	White PS	White PS	White or black	White PS
Door color/type	Alum. Frame	Alum. Frame	Plastic frame, black	Alum. frame	Alum. Frame	Plastic frame, black
Lock	No	No	No	Yes	Yes	No
Wheels	No	No	2 in back	2 in back	2 in back	No
Defrost & removal of water	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Noise	> 45	<45	<45	<45	<45	<45
Insulation, mm	35	35	45	38	38	45
Side change of door possible	Yes	Yes	Yes	Yes	Yes	Yes
Possible to build in	No	Yes	No	No	No	No
SHIPPING						
Quantity in standard truck	180	180	108	57	57	80
Quantity in 20 ft container	68	48	27	27	27	27
Quantity in 40 ft HC container	225	162	96	51	51	57

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DISPLAY COOLERS

UPRIGHT



M205



MS185



MFG95



MFG185

DISPLAY COOLERS




DIMENSIONS	M205	MS185	MFG95	MFG185
Outer dimensions, HxWxD, mm	2065x595x655	1795x595x600	821x595x561	1850x595x610
PACKAGING				
Dimensions HxWxD, mm	2215x615x675	1935x640x615	880x660x655	1925x636x671
VOLUME				
Volume, Gross, L	472	373	156	344
Volume, Net, L	451	358	-	285
Capacity 0,33 L cans	476	476	140	448
Capacity 0,5 L bottles	406	406	-	-
WEIGHT				
Weight, Gross, kg	73	80	51	88
Weight, Net, kg	71	71	46	86
SHELVES				
No. of shelves, pcs	5	5	3	6
Max. load, kg	35	25	29	25
Shelf material	White wire	White wire	Wire	Steel
COOLING SYSTEM				
Refrigerant	R600a	R600a	R600a	R600a
Climate class	3	3	3	3
Temperature range, °C	+1 to +9	+1 to +9	+3 to +18	+2 to +10
Type of thermostat	Mechanical	Electronical	Electronic	Electronic
Static/Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
ELECTRICAL				
Voltage, V	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50
Electronic display	No	Yes	Yes	Yes
ENERGY				
Energy consumption, kWh/24h	1,77	0,871	0,489	1,68
Energy consumption, kWh/year	646	318	178	613
Energy class	C	B	B	D
EEL	29	19,5	16,1	40
FEATURES				
Light inside top	Yes	Yes	No	Yes
Light in door side	Yes	No	No	Yes
Cabinet color (All PS)	White	White	Black	Black
Inside color	White, metal	White PS	Black PS	Black PS
Door color/type	Plastic frame, black	White, solid	Black full glass	Black full glass
Lock	No	No	No	Yes
Wheels	No	No	No	2 in back
Defrost & removal of water	Automatic	Automatic	Automatic	Automatic
Noise	<45	<45	<45	<45
Insulation, mm	45	45	38	38
Side change of door possible	Yes	Yes	Yes	Yes
Possible to build in	No	No	Yes	No
SHIPPING				
Quantity in standard truck	80	180	180	80
Quantity in 20 ft container	27	27	48	27
Quantity in 40 ft HC container	57	162	162	57

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DISPLAY COOLERS

CAN COOLERS



CC45



CC61

DISPLAY COOLERS



CONSTRUCTION		CC45	CC61
Dimensions HxWxD, mm		825xØ454	932xØ454
Packaging dimensions HxWxD, mm		900x550x550	1007x550x550
Packaging weight, kg		2,3	-
Weight, kg		29 / 26	36 / 33
STORAGE			
Volume, L		45 / 45	61 / 59
Capacity Wine bottles (0,75l)		16	-
Capacity 0,5 l bottles		-	54
Capacity 0,33 l cans		-	80
No. of shelf		-	2
Shelf dimension, mm		-	ø373x243
Shelf material		-	Steel, PE powder white
COOLING SYSTEM			
Refrigerant / amount, g		R600a / 51	R600a / 55
Temperature class		N	3K4
Noise, dB		39	45
Voltage, V		220-240	220-240
Frequency, Hz		50	50
Temperature range, °C		+2 to +8	+2 to +8
Energy consumption, kWh/24h		0,159	0,3
Energy class		D	B
FEATURES			
Lid color/type		Transparent	-
Cabinet color		Silver	Silver
Inside color/material		Grey / Steel	White / Prepainted Steel
Wheels		Yes	-

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

STORAGE COOLERS



DCG274

STORAGE COOLERS



CONSTRUCTION		DCG274
Dimensions HxWxD, mm		850x920x600
Packaging dimensions HxWxD, mm		960x960x700
Packaging weight, kg		2,44
Weight, Gross/Net, kg		50 / 45
STORAGE		
Volume, L		264 / 210
Capacity 0,33 l cans		388
COOLING SYSTEM		
Refrigerant / amount, g		R600a / 86
Temperature class		3M2
Noise, dB		38
Voltage, V		220-240
Frequency, Hz		50
Temperature range, °C		+4 to +12
Energy consumption, kWh/24h		0,484
Energy class		A
FEATURES		
Lid type		Glass
Cabinet color		White
Inside color/material		White / Steel
Lock		Yes

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

WINE CABINETS


W & WFG



WFG18



WFG22



WFG24



WFG32



WFG47

WINE CABINETS

DIMENSIONS	WFG18	WFG22	WFG24	WFG32	WFG47
Outer dimensions, HxWxD, mm	820x295x561	455x590x557	596x590x562	830x493x577	820x595x562
PACKAGING					
Dimensions HxWxD, mm	860x335x640	510x640x640	650x640x640	880x550x650	880x655x665
VOLUME					
Volume, Net, L	58	54	65	114	134
Capacity 0,75 L wine bottles	19	24	24	38	44
WEIGHT					
Weight, Gross, kg	29	33	41	47	53
Weight, Net, kg	27	30	38	43	48
SHELVES					
No. of shelves, pcs	6	3	3	6	5
Max. load, kg	5	13	13	15	18
Shelf dimensions, mm	430x229; 294x213	474x311	464x304	421x434; 421x296	526x442; 500x292
Shelf material	Wood	Wood	Wood	Steel+wood trim	Wood
COOLING SYSTEM					
Refrigerant	R600a	R600a	R600a	R600a	R600a
Refrigerant amount, gr.	25	23	35	30	35
Temperature class	-	-	-	-	-
Climate class, EN15502	N/ST	N/ST	N/ST	N/ST	N/ST
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic
Dual zone	No	No	Yes	Yes	Yes
Temperature range, °C	+5 to +20	+5 to +20	+5 to +10 / +10 to +18	+5 to +10 / +10 to +18	+5 to +10 / +10 to +18
Static/Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
ELECTRICAL					
Voltage, V	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50
Electronic display	Yes	Yes	Yes	Yes	Yes
Input power, watt	-	-	-	-	-
ENERGY					
Energy consumption, kWh/24h	0,268	0,273	0,342	0,389	0,397
Energy consumption, kWh/year	97,82	100	125	142	145
Energy class	F	F	G	G	G
EEl	124	124	154	171	171
FEATURES					
Light inside top	Yes	Yes	Yes	Yes	Yes
Light in door side	No	No	No	No	No
Cabinet color (All PS)	Black	Black	Black	Black	Black
Inside color	Black/PS	Black/PS	Black/PS	Black/PS	Black/PS
Door color/ type	Black full glass	Black full glass	Black full glass	Black full glass	Black full glass
Lock	No	No	No	No	Yes
Feet	Yes	Yes	Yes	Yes	Yes
Defrost & removal of water	Automatic	Automatic	Automatic	Automatic	Automatic
Noise	39	37	39	39	39
Insulation, mm	35	35	35	35	35
Side change of door possible*	Yes	Yes	Yes	Yes	Yes
Possible to build in	Yes	Yes	Yes	No	Yes
SHIPPING					
Quantity in standard truck	441	315	252	252	180
Quantity in 20 ft container	122	108	81	68	48
Quantity in 40 ft HC container	366	270	216	225	162

*to be done by technician

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

WINE CABINETS

WFG



WFG48



WFG49



WFG155



WFG185



W185


WINE CABINETS



DIMENSIONS	WFG48	WFG49	WFG155	WFG185	W185
Outer dimensions, HxWxD, mm	820/860x595x562	820/860x595x562	1550x595x595	1850x595x610	1850x595x595
PACKAGING					
Dimensions HxWxD, mm	880x655x665	910x655x655	-	-	1925x636x671
VOLUME					
Volume, Net, L	120	120	338	414	414
Capacity 0,75 L wine bottles	34	34	147	197	187
WEIGHT					
Weight, Gross, kg	53	55	76	85	84
Weight, Net, kg	48	50	74	83	82
SHELVES					
No. of shelves, pcs	4	4	5	6	4+1+1
Max. load, kg	15	15	85	85	65
Shelf dimensions, mm	510x426	510x426	523x440;523x-360;523x230	523x440;523x-360;523x230	523x440;523x-360;523x230
Shelf material	Wood	Wood	Oak	Oak	Beech
COOLING SYSTEM					
Refrigerant	R600a	R600a	R600a	R600a	R600a
Refrigerant amount, gr.	35	35	56	79	79
Temperature class	-	-	-	-	-
Climate class, EN15502	N/ST	N/ST	SN/ST/T/N	SN-ST-N	SN-ST-N
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic
Dual zone	Yes	Yes	Yes- no divider	Yes-no divider	Yes-no divider
Temperature range, °C	+5 to +10 / +10 to +18	+5 to +10 / +10 to +18	+5 to +20	+5 to +20	+5 to +22
Static/Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
ELECTRICAL					
Voltage, V	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50
Electronic display	Yes	Yes	Yes	Yes	Yes
Input power, watt	-	-	200	200	200
ENERGY					
Energy consumption, kWh/24h	0,369	0,369	0,455	0,474	0,479
Energy consumption, kWh/year	135	135	166	173	175
Energy class	G	G	G	G	G
EEl	162	162	173	171	173
FEATURES					
Light inside top	No	No	Yes	Yes	Yes
Light in door side	Both sides	Both sides	Yes	Yes	?
Cabinet color (All PS)	Black	Black	Black	Black	Black
Inside color	Black/PS	Black/PS	Black/PS	Black/PS	Black/PS
Door color/ type	Black full glass	Black full glass	Black full glass	Black full glass	Black/ alu sides
Lock	No	No	Yes	Yes	Yes
Feet	Yes	Yes	Yes	Yes	Yes
Defrost & removal of water	Automatic	Automatic	Automatic	Automatic	Automatic
Noise	39	39	40	39	39
Insulation, mm	35	35	35	35	35
Side change of door possible*	Yes	Yes	Yes	Yes	Yes
Possible to build in	Yes	Yes	Yes	Yes	Yes
SHIPPING					
Quantity in standard truck	180	180	57	57	57
Quantity in 20 ft container	48	48	27	27	27
Quantity in 40 ft HC container	162	150	51	51	51

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DISPLAY FREEZERS



MF180



DFG205



DFG275



DFG405



DFG505

DISPLAY FREEZERS



DIMENSIONS	MF180	DFG205	DFG275	DFG405	DFG505
Outer dimensions, HxWxD, mm	1860x600x595	905x730x610	905x930x610	905x1270x610	905x1570x610
Inner dimensions, HxWxD, mm		700x620x500	700x820x500	700x1160x500	700x1460x500
PACKAGING					
Dimensions HxWxD, mm	1925x636x670	960x765x710	960x965x710	960x1305x710	960x1605x710
VOLUME					
Volume, Gross, L	282	194	265	386	492
Volume, Net, L	235	154	210	307	394
WEIGHT					
Weight, Gross, kg	90	50	54	61	76
Weight, Net, kg	88	47	51	58	73
SHELVES					
No. of shelves, pcs	5+1	-	-	-	-
Max. load, kg	25	-	-	-	-
Shelf material	White wire	-	-	-	-
COOLING SYSTEM					
Ambient temperature, °C	-	+10 to +30	+10 to +30	+10 to +30	+10 to +30
Refrigerant	R290	R600a	R600a	R600a	R600a
Refrigerant amount, gr	-	90	90	115	102
Climate class	3	4	4	4	4
Temperature range, °C	-18 to -24	-18 to -24	-18 to -24	-18 to -24	-18 to -24
Type of thermostat	Electronic	-	-	-	Mechanical
Static/Ventilated	Ventilated	Static	Static	Static	Static
ELECTRICAL					
Voltage, V	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50
Electronic display	Yes	-	-	-	Yes
Type of thermometer	-	Digital	Digital	Digital	Digital
Type of thermostat	-	Mechanical	Mechanical	Mechanical	Mechanical
ENERGY					
Energy consumption, kWh/24h	13.3	1.76	2.33	2.25	3.54
Energy consumption, kWh/year	4855	641	850	821	1292
Energy class	F	C	C	C	C
EEI	79	22.0	26.0	22.5	28.0
Input power, watt	-	-	-	-	-
FEATURES					
Light inside top	No	-	-	-	-
Light in door side	Yes	-	-	-	-
Cabinet color (All PS)	White	White	White	White	White
Inside color	White PS	Hammered aluminum	Hammered aluminum	Hammered aluminum	Hammered aluminum
Door color/type	Alum.frame glass	Sliding glass	Sliding glass	Sliding glass	Sliding glass
Lock	Yes	Yes	Yes	Yes	Yes
Wheels	2 in back	Castors	Castors	Castors	Castors
Defrost & removal of water	Automatic	Manual	Manual	Manual	Manual
Noise	50	50	50	50	50
Insulation, mm	50	-	-	-	-
Side change of door possible	Yes	-	-	-	-
Possible to build in	No	-	-	-	-
OPTION					
Graphics	-	Option	Option	Option	Option
Baskets	-	2	3	4	5
SHIPPING					
Quantity in standard truck	57	-	126	60	54
Quantity in 20 ft container	27	48	-	-	-
Quantity in 40 ft HC container	57	141	105	79	71

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

STORAGE FREEZERS



MF185



HF271



HF396



HF506

STORAGE FREEZERS




DIMENSIONS	MF185	HF271	HF396	HF506
Outer dimensions, HxWxD, mm	1850x595x600	850x960x695	850x1260x695	850x1560x600
Inner dimensions, HxWxD, mm	-	670x820x500	670x1160x500	670x1460x500
PACKAGING				
Dimensions HxWxD, mm	1920x642x672	888x985x716	888x1302x716	888x1602x716
VOLUME				
Volume, Gross, L	308	256	373	476
Volume, Net, L	276	206	302	384
WEIGHT				
Weight, Gross, kg	78	50	57	64
Weight, Net, kg	71	48	55	60
BASKETS				
No. of baskets/shelves, pcs	7 drawers	1	2	2
Max. load, kg	20	-	-	-
Shelf material	White wire	-	-	-
TEMPERATURE				
Ambient temperature, °C	-	+10 to +35	+10 to +35	+10 to +35
Climate class	3	7	7	7
Temperature range, °C	-18 to -24	-18 to -24	-18 to -24	-18 to -24
COOLING SYSTEM				
Refrigerant, type	R660a	R600a	R600a	R600a
Refrigerant amount, gr	-	84	90	106
Static/ventilated	Static	Static	Static	Static
ELECTRICAL				
Voltage, V	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50
Voltage 110/60, V-Hz	N/A	N/A	Option	Option
Type of thermometer	-	Mechanical	Mechanical	Mechanical
Type of thermostat	Mechanical	Mechanical	Mechanical	Mechanical
Electronic display	Yes	-	-	-
ENERGY				
Energy consumption, kWh/24h	0,61	1,62	1,84	2,21
Energy consumption, kWh/year	223	591	672	807
Energy class	E	D	D	D
EEL	99	41,3	38,2	39,6
Input power, watt	-	-	-	-
FEATURES				
Light inside top	No	White	White	White
Light in door side	No	Hammered aluminum	Hammered aluminum	Hammered aluminum
Cabinet color (All PS)	White	White, lift up	White, lift up	White, lift up
Inside color	White	Stainless	Stainless	Stainless
Door color/type	Solid white	-	-	-
Lock	No	Yes	Yes	Yes
Wheels/Castors/Feet	No	Feet	Feet	Feet
Defrost & removal of water	Automatic	Manual	Manual	Manual
Noise	41	-	-	-
Insulation, mm	45	50	50	50
Side change of door possible	Yes	-	-	-
Possible to build in	No	-	-	-
OPTION				
Graphics	-	Option	Option	Option
Baskets	-	3	6	7
SHIPPING				
Quantity in standard truck	63	141	90	81
Quantity in 20 ft container	27	-	-	-
Quantity in 40 ft HC container	54	105	79	70

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

STORAGE FREEZERS

WITH LIFT UP LID



SB110 – SB500

STORAGE FREEZERS



DIMENSIONS	SB 110	SB 220	SB 290	SB 370	SB 430	SB 500
Outer dimensions, HxWxD, mm	850x550x650	860x890x690	860x1090x690	860x1320x690	860x1510x690	860x1700x690
Inner dimensions, HxWxD, mm	690x390x490	690x730x490	690x930x490	690x1160x490	690x1350x490	690x1540x490
PACKAGING						
Dimensions HxWxD, mm	890x590x660	880x950x710	880x1140x710	880x1370x710	880x1510x710	880x1700x710
VOLUME						
Volume, Gross, L	102	211	278	352	414	476
Volume, Net, L	99	209	275	349	411	472
WEIGHT						
Weight, Gross, kg	23	39	47	51	57	63
Weight, Net, kg	21	37	44	48	53	58
BASKETS						
No. of baskets, pcs	0	1	1	2	2	2
TEMPERATURE						
Ambient temperature, °C	+10 to +40	+10 to +35	+10 to +35	+10 to +35	+10 to +35	+10 to +35
Climate class	7	7	7	7	7	7
Temperature range, °C	-17 to -25	-17 to -25	-17 to -25	-17 to -25	-17 to -25	-17 to -25
COOLING SYSTEM						
Refrigerant, type	R600a	R600a	R600a	R600a	R600a	R600a
Refrigerant amount, gr	33	43	50	55	67	72
Static/ventilated	Static	Static	Static	Static	Static	Static
Freezing capacity, kg/24h	11	16	24	23	24	24
ELECTRICAL						
Voltage, V	220-240	220-240	220-240	220-240	220-240	220-240
Voltage 110/60, V-Hz	Option	Option	Option	Option	Option	Option
Frequency, Hz	50	50	50	50	50	50
Type of thermometer	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
ENERGY						
Energy consumption, kWh/24h	0,6	0,81	0,91	1,052	1,239	1,484
Energy consumption, kWh/year	219	296	332	384	452	542
Energy class	B	B	B	B	C	C
EEl	19,9	19,7	19,3	19,3	20,4	22,2
Input power, watt	-	-	-	-	-	-
FEATURES						
Cabinet color	White	White	White	White	White	White
Inside material/color	Hammered aluminum	Hammered aluminum	Hammered aluminum	Hammered aluminum	Hammered aluminum	Hammered aluminum
Door or lid color/type	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up
Alternative lid	Stainless	Stainless	Stainless	Stainless	Stainless	Stainless
Lock	Yes	Yes	Yes	Yes	Yes	Yes
Castors/feet	Feet	Feet	Feet	Feet	Feet	Feet
Defrost & removal of water	Manual	Manual	Manual	Manual	Manual	Manual
Insulation, mm	55	65	65	65	65	65
OPTION						
Graphics	Option	Option	Option	Option	Option	Option
Baskets / max no.	1	3	3+1*	4+1*	5+1*	6
SHIPPING						
Quantity in standard truck	252	135	114	90	81	72
Quantity in 20 ft container	88	42	40	28	25	18
Quantity in 40 ft HC container	216	112	96	75	69	60

*remove internal partition

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

STORAGE FREEZERS

WITH LIFT UP LID



SB 200



SB 300



SB 400

STORAGE FREEZERS




DIMENSIONS	SB 200	SB 300	SB 400
Outer dimensions, HxWxD, mm	850x920x600	850x1260x600	850x1560x600
Inner dimensions, HxWxD, mm	635x760x440	635x1100x440	635x1400x440
PACKAGING			
Dimensions HxWxD, mm	888x962x716	888x1302x716	888x1602x716
VOLUME			
Volume, Gross, L	198	296	383
Volume, Net, L	189	284	368
WEIGHT			
Weight, Gross, kg	48	60	68
Weight, Net, kg	45	57	65
BASKETS			
No. of baskets, pcs	2	4	5
TEMPERATURE			
Ambient temperature, °C	+10 to +35	+10 to +35	+10 to +30
Climate class	7	7	7
Temperature range, °C	-18 to -24	-18 to -24	-18 to -24
COOLING SYSTEM			
Refrigerant, type	R600a	R600a	R600a
Refrigerant amount, gr	55	78	95
Static/ventilated	Static	Static	Static
ELECTRICAL			
Voltage, V	220-240	220-240	220-240
Frequency, Hz	50	50	50
Type of thermometer	Digital	Digital	Digital
Type of thermostat	Mechanical	Mechanical	Mechanical
ENERGY			
Energy consumption, kWh/24h	0,68	0,99	1,17
Energy consumption, kWh/year	248	361	427
Energy class	B	C	C
EEl	18,7	21,8	23,0
Input power, watt	-	-	-
FEATURES			
Cabinet color	White	White	White
Inside material/color	Hammered aluminum	Hammered aluminum	Hammered aluminum
Door or lid color/type	White, lift up	White, lift up	White, lift up
Alternative lid	Stainless	Stainless	Stainless
Lock	Yes	Yes	Yes
Castors/feet	Feet	Feet	Feet
Defrost & removal of water	Manual	Manual	Manual
Insulation, mm	80	80	80
OPTION			
Graphics	Option	Option	Option
Baskets	3	5	6
SHIPPING			
Quantity in standard truck	94	60	54
Quantity in 20 ft container			
Quantity in 40 ft HC container	108	81	72

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

LOW TEMPERATURE

WITH LIFT UP LID



VT146



VT206



VT306



VT406



VT546

LOW TEMPERATURE




CONSTRUCTION	VT146	VT206	VT306	VT406	VT546
Outer Dimensions, HxWxD, mm	885x725x605	885x923x605	885x1265x605	885x1562x605	885x1664x605
Inner Dimensions, HxWxD, mm	635x560x440	635x760x440	635x1100x440	635x1400x440	635x1500x440
PACKAGING					
Dimensions HxWxD, mm	-	-	-	-	-
VOLUME					
Volume, Gross, L	140	198	296	384	495
Volume, Net, L	140	198	296	384	495
WEIGHT					
Weight, Gross, kg	55	63	77	83	108
Weight, Net, kg	51	58	71	77	92
BASKETS					
No. of baskets, pcs	1	1	1	1	1
TEMPERATURE					
Ambient temperature, °C	+10 to +35	+10 to +35	+10 to +30	+10 to +35	+10 to +35
Climate class	-	-	-	-	-
Temperature range, °C	-10 to -45	-10 to -45	-10 to -45	-10 to -45	-10 to -45
COOLING SYSTEM					
Refrigerant, type	R290	R290	R290	R290	R290
Refrigerant amount, gr	-	-	-	-	-
Static/ventilated	Static	Static	Static	Static	Static
ELECTRICAL					
Voltage, V	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50
Voltage 110/60, V-Hz	Option	Option	Option	Option	Option
Type of thermometer	Electronic	Electronic	Electronic	Electronic	Electronic
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic
Potential free contact for remote control	Yes	Yes	Yes	Yes	Yes
Porthole for sensor, ø12 mm	Yes	Yes	Yes	Yes	Yes
ENERGY					
Energy consumption, kWh/24h	1,865	3,14	3,74	4,09	4,16
Energy consumption, kWh/year	-	-	-	-	-
Energy class	not needed	not needed	not needed	not needed	not needed
EEL	not needed	not needed	not needed	not needed	not needed
Input power, watt	415	415	415	415	415
FEATURES					
Cabinet color	White	White	White	White	White
Inside material/color	White painted steel	White painted steel	White painted steel	White painted steel	White painted steel
Door or lid color/type	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up
Alternative lid	n/a	n/a	n/a	n/a	n/a
Lock	Yes	Yes	Yes	Yes	Yes
Castors/feet	Castors	Castors	Castors	Castors	Castors
Defrost & removal of water	Manual	Manual	Manual	Manual	Manual
Insulation, mm	80	80	80	80	80
OPTION					
Graphics	Option	Option	Option	Option	Option
Baskets	-	-	-	-	-
SHIPPING					
Quantity in standard truck	216	168	120	96	96
Quantity in 20 ft container	-	-	-	-	-
Quantity in 40 ft HC container	94	78	54	42	38

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

LOW TEMPERATURE

WITH LIFT UP LID



VT75



VT147



VT207



VT307



VT407



VT547

LOW TEMPERATURE



CONSTRUCTION	VT75	VT147	VT207	VT307	VT407	VT547
Outer Dimensions, HxWxD, mm	870x555x555	885x725x605	885x923x605	885x1265x605	885x1562x605	885x1664x605
Inner Dimensions, HxWxD, mm	465x390x390	635x560x440	635x760x440	635x1100x440	635x1400x440	635x1500x440
PACKAGING						
Dimensions HxWxD, mm	-	-	-	-	-	-
VOLUME						
Volume, Gross, L	-	140	198	296	384	495
Volume, Net, L	-	140	198	296	384	495
WEIGHT						
Weight, Gross, kg	48	55	63	77	83	108
Weight, Net, kg	42	51	58	71	77	92
BASKETS						
No. of baskets, pcs	1	1	1	3	4	3
TEMPERATURE						
Ambient temperature, °C	+10 to +30	+10 to +30	+10 to +30	+10 to +30	+10 to +30	+10 to +30
Climate class	-	-	-	-	-	-
Temperature range, °C	-40 to -60	-40 to -60	-40 to -60	-40 to -60	-40 to -60	-40 to -60
COOLING SYSTEM						
Refrigerant, type	Mix of hydrocarbons	Mix of hydrocarbons	Mix of hydrocarbons	Mix of hydrocarbons	Mix of hydrocarbons	Mix of hydrocarbons
Refrigerant amount, gr	-	-	-	-	-	-
Static/ventilated	Static	Static	Static	Static	Static	Static
ELECTRICAL						
Voltage, V	220-240	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50	50
Voltage 110/60, V-Hz	Option	Option	Option	Option	Option	Option
Type of thermometer	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Potential free contact for remote control	Yes	Yes	Yes	Yes	Yes	Yes
Porthole for sensor, ø12 mm	Yes	Yes	Yes	Yes	Yes	Yes
ENERGY						
Energy consumption, kWh/24h	2,2	3,71	3,12	5,56	7,08	5,78
Energy consumption, kWh/year	-	-	-	-	-	-
Energy class	not needed	not needed	not needed	not needed	not needed	not needed
EEl	not needed	not needed	not needed	not needed	not needed	not needed
Input power, watt	415	415	-	-	-	-
FEATURES						
Cabinet color	White	White	White	White	White	White
Inside material/color	White painted steel	White painted steel	White painted steel	White painted steel	White painted steel	White painted steel
Door or lid color/type	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up
Alternative lid	n/a	n/a	n/a	n/a	n/a	n/a
Lock	Yes	Yes	Yes	Yes	Yes	Yes
Castors/feet	Feet	Castors	Castors	Castors	Castors	Castors
Defrost & removal of water	Manual	Manual	Manual	Manual	Manual	Manual
Insulation, mm	80	80	80	80	80	80
OPTION						
Graphics	Option	Option	Option	Option	Option	Option
Baskets	-	-	-	-	-	-
SHIPPING						
Quantity in standard truck	288	216	168	120	96	96
Quantity in 20 ft container	-	-	-	-	-	-
Quantity in 40 ft HC container	114	94	78	54	42	38

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

QUALITY COOLING APPLIANCES



Vestfrost Solutions

Falkevej 12
6705 Esbjerg Ø
Denmark

+45 79 14 22 22

LML@vestfrostsolutions.com

BNE@vestfrostsolutions.com



Please see our website
for more information:

www.vestfrostsolutions.com

www.vestfrostsolutions.com/food/



www.linkedin.com/company/vestfrostsolutions



www.youtube.com/@vestfrostsolutionsDK

VESTFROST
SOLUTIONS