

PRODUCT OVERVIEW

FOOD SOLUTIONS





VESTFROST FOOD

PROFESSIONAL COOLING SOLUTIONS

**Designed to ensure optimal preservation and presentation,
maintaining the perfect temperature to guarantee freshness and flavor.**

Cooling with confidence

CONTENT


VESTFROST SOLUTIONS – FOOD

DISPLAY COOLERS +0°C TO +18°C	4-9
STORAGE COOLERS +4°C TO +12°C	10-11
WINE CABINETS +5°C TO +22°C	12-15
DISPLAY FREEZERS -18°C TO -24°C	16-17
STORAGE FREEZERS -14°C TO -25°C	18-23
LOW TEMP. CHEST FREEZERS -10°C TO -45°C	24-25
LOW TEMP. CHEST FREEZERS -40°C TO -60°C	26-27

CHILLING PRECISION

DISPLAY COOLERS

UPRIGHT



M25



M65



M80



M85



M95



M140



M150

DISPLAY COOLERS



DIMENSIONS	M25	M65	M80	M85	M95	M140	M150
Outer dimensions, WxDxH, mm	359x428x505	432x515x675	380x544x903	493x588x841	595x572x821	380x544x1247	600x595x1560
PACKAGING							
Dimensions, WxDxH, mm	410x470x535	490x545x715	440x610x990	550x650x880	655x660x880	440x610x1330	636x671x1625
VOLUME							
Volume, Gross, L	22	60	84	138	164	126	281
Volume, Net, L	20	55	84	124	146	144	193
Capacity 0,33 L cans	-	-	-	140	140	-	343
Capacity 0,5 L bottles	-	-	-	-	-	-	189
WEIGHT							
Weight, Gross, kg	21,5	29	34,9	39	49	45,7	73
Weight, Net, kg	20	26	30,2	35	44	39,8	71
SHELVES							
No. of shelves, pcs	1	2	2	2+1	3	4	4+1
Max. load, kg	6	15	15	25	29	15	25
Shelf material	-	-	-	Black wire	Black wire	-	White wire
COOLING SYSTEM							
Refrigerant	R600a	R600a	R600a	R600a	R600a	R600a	R600a/50g
Climate class	CC2	CC2	CC2	3	3	CC2	3
Temperature range, °C	+0 to +7	+0 to +7	+0 to +7	+2 to +10	+2 to +10	+0 to +7	+2 to +10
Type of thermostat	20	30	24	Electronic	Electronic	32	Electronic
Static/Ventilated	-	-	-	Ventilated	Ventilated	-	Ventilated
ELECTRICAL							
Voltage, V	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50	50	50
Electronic display	No	No	No	Yes	Yes	No	Yes
ENERGY							
Energy consumption, kWh/24h	0,31	0,45	0,82	0,498	0,489	0,96	2,047
Energy consumption, kWh/year	-	-	-	182	182	-	747
Energy class	B	B	C	B	B	C	B
EEL	13,8	18,1	31,1	18	18	32,9	13,4
FEATURES							
Light inside top	Yes	Yes	Yes	Yes	Yes	Yes	No
Light in door side	2	2	2	No	No	2	Yes
Cabinet color (All PS)	Black	Black	Black	Black	Black	Black	White
Inside color	White / Pre-coated AL	White / Pre-coated AL	White / Pre-coated AL	Black PS	Black PS	White / Pre-coated AL	White PS
Door color/type	Glass	Glass	Glass	Alum. Frame	Alum. Frame	Glass	Alum. frame
Lock	Yes	Yes	Yes	No	No	Yes	Yes
Wheels	No	No	No	No	No	No	2 in back
Defrost & removal of water	-	-	-	Automatic	Automatic	-	Automatic
Noise	≤45	≤45	≤45	> 45	<45	≤45	<45
Insulation, mm				35	35		38
Side change of door possible				Yes	Yes		Yes
Possible to build in				No	Yes		No
SHIPPING							
Quantity in standard truck	-	-	-	180	180	-	57
Quantity in 20 ft container	-	-	-	68	48	-	27
Quantity in 40 ft HC container	-	-	-	225	162	-	51

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DISPLAY COOLERS

UPRIGHT



M180



MS70



MFG95



MFG185

DISPLAY COOLERS




DIMENSIONS	M180	MS70	MFG95	MFG185
Outer dimensions, WxDxH, mm	600x595x1860	460x430x816	595x561x821	595x610x1850
PACKAGING				
Dimensions, WxDxH, mm	671x636x1925	510x510x870	660x655x880	636x671x1925
VOLUME				
Volume, Gross, L	350	67,5	156	344
Volume, Net, L	255	43		285
Capacity 0,33 L cans	441	-	140	448
Capacity 0,5 L bottles	231	-	-	-
WEIGHT				
Weight, Gross, kg	81	27,5	51	88
Weight, Net, kg	79	25	46	86
SHELVES				
No. of shelves, pcs	5+1	3	3	6
Max. load, kg	25	5	29	25
Shelf material	White wire		Wire	Steel
COOLING SYSTEM				
Refrigerant	R600a/50g	R600a	R600a	R600a/60g
Climate class	3	CC2	3	3
Temperature range, °C	+1 to +7	+0 to +7	+3 to +18	+2 to +10
Type of thermostat	Electronic	20	Electronic	Electronic
Static/Ventilated	Ventilated		Ventilated	Ventilated
ELECTRICAL				
Voltage, V	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50
Electronic display	Yes	No	Yes	Yes
ENERGY				
Energy consumption, kWh/24h	2,381	0,236	0,498	1,68
Energy consumption, kWh/year	869		182	613
Energy class	B	A	B	D
EEL	15	9,4	18	40
FEATURES				
Light inside top	No	Yes	No	Yes
Light in door side	Yes	0	No	Yes
Cabinet color (All PS)	White or black	White	Black	Black
Inside color	White or black	White / PS	Black PS	Black PS
Door color/type	Alum. Frame	Foamed	Black full glass	Black full glass
Lock	Yes	Yes	Yes	Yes
Wheels	2 in back	No	No	2 in back
Defrost & removal of water	Automatic	-	Automatic	Automatic
Noise	<45	37	<45	<45
Insulation, mm	38	-	38	38
Side change of door possible	Yes	-	Yes	Yes
Possible to build in	No	-	Yes	No
SHIPPING				
Quantity in standard truck	57	-	180	80
Quantity in 20 ft container	27	-	48	27
Quantity in 40 ft HC container	51	-	162	57

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DISPLAY COOLERS

CAN COOLERS



CC45



CC61




**CC75
back-up**

DISPLAY COOLERS


CONSTRUCTION	CC45	CC61	CC75 Back-up
Dimensions WxDxH, mm	ø454x825	ø450x950	ø569x850
Packaging dimensions WxDxH, mm	550x550x900	550x550x1007	585x585x895
Packaging weight, kg	2,3	-	-
Weight, Gross/net, kg	29 / 26	36 / 33	36,5 / 30
STORAGE			
Volume, L	45 / 45	61 / 59	67 / 98
Capacity Wine bottles (0,75L)	16	-	-
Capacity 0,33 l cans	-	80	98
Capacity 0,5 l bottles	-	54	-
No. of shelf	-	2	-
Shelf dimension, mm	-	ø373x243	-
Shelf material	-	Steel+ white PE	-
COOLING SYSTEM			
Refrigerant / amount, g	R600a / 51	R600a / 45	R600a
Climate class	4	CC1 K4	CC2
Temperature range, °C	+2 to +8	+2 to +8	+1 to +9
Type of thermostat	Mechanical	Mechanical	41
Static / ventilated	Ventilated	Ventilated	-
Voltage, V	220-240	220-240	220-240
Frequency, Hz	50	50	50
Electronic display	No	No	No
Energy consumption, kWh/24h	0,159	0,361	0,39
Energy consumption, kWh/year	58	132	-
Energy class	D	B	B
EEl	-	-	15,5
FEATURES			
Light inside top	-	Option	NO
Light in door side	-	No	-
Cabinet color- all painted steel	Grey	Grey	Black
Inside color	White	White	Grey / Precoated AL
Door color/ type	2 x flap	2 x flap	Glass
Lock	No	No	No
Wheels	4	4	Yes
Defrost & removal of water	Yes	Yes	-
Noise, dB	39	45	≤45
Insulation, mm	38	38	-
Side change of door possible	No	No	-
Possible to build in	No	No	-
FEATURES			
Quantity in standard truck	-	176	-
Quantity in 20 ft container	-	-	-
Quantity in 40 ft HC container	-	-	-

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

STORAGE COOLERS



DCG274



DCG274 PP

STORAGE COOLERS



DIMENSIONS	DCG274	DCG274 PP
Outer dimensions, WxDxH, mm	930x610x905	930x610x905
Inner dimensions, WxDxH, mm	820x500x700	820x500x700
PACKAGING		
Dimensions WxDxH, mm	965x710x960	965x710x960
VOLUME		
Volume, Gross, L	265	265
Volume, Net, L	210	210
WEIGHT		
Weight, Gross, kg	54	54
Weight, Net, kg	51	51
BASKETS		
No. of baskets/shelves, pcs	0	0
Max. load, kg	-	-
Shelf material	-	-
TEMPERATURE		
Ambient temperature, °C	+10 to +30	+10 to +30
Climate class	4	4
Temperature range, °C	+4 to +12	+4 to +12
COOLING SYSTEM		
Refrigerant, type	R600a	R600a
Refrigerant amount, gr	86	86
Static/ventilated	Static	Static
ELECTRICAL		
Voltage, V	220-240	220-240
Frequency, Hz	50	50
Voltage 110/60, V-Hz	N/A	N/A
Type of thermometer	Digital	Digital
Type of thermostat	Mechanical	Mechanical
Electronic display	-	-
ENERGY		
Energy consumption, kWh/24h	0,484	0,484
Energy consumption, kWh/year	177	177
Energy class	A	A
EEl	9,8	9,8
FEATURES		
Cabinet color	White	White
Inside material/color	Hammered aluminum	Hammered aluminum
Door color/type	Sliding glass	Sliding glass
Lock	Yes	Yes
Wheels/Castors/Feet	Castors	Castors
Defrost & removal of water	Manual	Manual
Noise	-	-
Insulation, mm	50	50
OPTION		
Graphics	Option	Option
Baskets - max. qty	3	3
SHIPPING		
Quantity in standard truck	126	126
Quantity in 20 ft container	-	-
Quantity in 40 ft HC container	105	105

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

WINE CABINETS

W & WFG



WFG18



WFG24



WFG32



WFG47

WINE CABINETS



DIMENSIONS	WFG18	WFG24	WFG32	WFG47
Outer dimensions, WxDxH, mm	295x561x820	590x562x596	493x577x830	595x562x820
PACKAGING				
Dimensions WxDxH, mm	335x640x860	640x640x650	550x650x880	655x665x880
VOLUME				
Volume, Net, L	58	65	114	134
Capacity 0,75 L wine bottles	19	24	38	44
WEIGHT				
Weight, Gross, kg	29	41	47	53
Weight, Net, kg	27	38	43	48
SHELVES				
No. of shelves, pcs	6	3	6	5
Max. load, kg	5	13	15	18
Shelf dimensions, mm	430x229; 294x213	464x304	421x434; 421x296	526x442; 500x292
Shelf material	Wood	Wood	Steel+wood trim	Wood
COOLING SYSTEM				
Refrigerant	R600a	R600a	R600a	R600a
Refrigerant amount, gr.	25	35	30	35
Climate class, EN15502	N/ST	N/ST	N/ST	N/ST
Type of thermostat	Electronic	Electronic	Electronic	Electronic
Dual zone	No	Yes	Yes	Yes
Temperature range, °C	+5 to +20	+5 to +10 / +10 to +18	+5 to +10 / +10 to +18	+5 to +10 / +10 to +18
Static/Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
ELECTRICAL				
Voltage, V	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50
Electronic display	Yes	Yes	Yes	Yes
ENERGY				
Energy consumption, kWh/24h	0,268	0,342	0,389	0,397
Energy consumption, kWh/year	97,82	125	142	145
Energy class	F	G	G	G
EEl	124	154	171	171
FEATURES				
Light inside top	Yes	Yes	Yes	Yes
Light in door side	No	No	No	No
Cabinet color (All PS)	Black	Black	Black	Black
Inside color	Black/PS	Black/PS	Black/PS	Black/PS
Door color/ type	Black full glass	Black full glass	Black full glass	Black full glass
Lock	No	No	No	Yes
Feet	Yes	Yes	Yes	Yes
Defrost & removal of water	Automatic	Automatic	Automatic	Automatic
Noise	39	39	39	39
Insulation, mm	35	35	35	35
Side change of door possible*	Yes	Yes	Yes	Yes
Possible to build in	Yes	Yes	No	Yes
SHIPPING				
Quantity in standard truck	441	252	252	180
Quantity in 20 ft container	122	81	68	48
Quantity in 40 ft HC container	366	216	225	162

*to be done by technician

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

WINE CABINETS

WFG



WFG48



WFG49



WFG155



WFG185



W185

WINE CABINETS



DIMENSIONS	WFG48	WFG49	WFG155	WFG185	W185
Outer dimensions, WxDxH, mm	595x562x820/860	595x562x820/860	595x595x1550	595x610x1850	595x595x1850
PACKAGING					
Dimensions WxDxH, mm	655x665x880	655x655x910	-	636x671x1925	636x671x1925
VOLUME					
Volume, Net, L	120	120	338	414	414
Capacity 0,75 L wine bottles	34	34	147	197	187
WEIGHT					
Weight, Gross, kg	53	55	76	85	84
Weight, Net, kg	48	50	74	83	82
SHELVES					
No. of shelves, pcs	4	4	5	6	4+1+1
Max. load, kg	15	15	65	65	65
Shelf dimensions, mm	510x426	510x426	523x440;523x-360;523x230	523x440;523x-360;523x230	523x440;523x-360;523x230
Shelf material	Wood	Wood	Oak	Oak	Oak
COOLING SYSTEM					
Refrigerant	R600a	R600a	R600a	R600a	R600a
Refrigerant amount, gr.	35	35	56	79	79
Climate class, EN15502	N/ST	N/ST	SN/ST/T/N	SN-ST-N	SN-ST-N
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic
Dual zone	Yes	Yes	Yes- no divider	Yes-no divider	Yes-no divider
Temperature range, °C	+5 to +10 / +10 to +18	+5 to +10 / +10 to +18	+5 to +20	+5 to +20	+5 to +22
Static/Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
ELECTRICAL					
Voltage, V	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50
Electronic display	Yes	Yes	Yes	Yes	Yes
ENERGY					
Energy consumption, kWh/24h	0,369	0,369	0,455	0,474	0,479
Energy consumption, kWh/year	135	135	166	173	175
Energy class	G	G	G	G	G
EEl	162	162	173	171	173
FEATURES					
Light inside top	No	No	Yes	Yes	Yes
Light in door side	Both sides	Both sides	Yes	Yes	No
Cabinet color (All PS)	Black	Black	Black	Black	Black
Inside color	Black/PS	Black/PS	Black/PS	Black/PS	Black/PS
Door color/ type	Black full glass	Black full glass	Black full glass	Black full glass	Black/ alu sides
Lock	No	No	Yes	Yes	Yes
Feet	Yes	Yes	Yes	Yes	Yes
Defrost & removal of water	Automatic	Automatic	Automatic	Automatic	Automatic
Noise	39	39	40	39	39
Insulation, mm	35	35	35	35	35
Side change of door possible*	Yes	Yes	Yes	Yes	Yes
Possible to build in	Yes	Yes	Yes	Yes	Yes
SHIPPING					
Quantity in standard truck	180	180	57	57	57
Quantity in 20 ft container	48	48	27	27	27
Quantity in 40 ft HC container	162	150	51	51	51

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DISPLAY FREEZERS



MF180



DFG205



DFG275



DFG405



DFG505

DISPLAY FREEZERS



DIMENSIONS	MF180	DFG205	DFG275	DFG405	DFG505
Outer dimensions, WxDxH, mm	600x595x1860	730x610x905	930x610x905	1270x610x905	1570x610x905
Inner dimensions, WxDxH, mm	468x445x1340	620x500x700	820x500x700	1160x500x700	1460x500x700
PACKAGING					
Dimensions WxDxH, mm	636x670x1925	765x710x960	965x710x960	1305x710x960	1605x710x960
VOLUME					
Volume, Gross, L	282	194	265	386	492
Volume, Net, L	235	154	210	307	394
WEIGHT					
Weight, Gross, kg	90	50	54	61	76
Weight, Net, kg	88	47	51	58	73
SHELVES					
No. of shelves, pcs	5+1	-	-	-	-
Max. load, kg	25	-	-	-	-
Shelf material	White wire	-	-	-	-
COOLING SYSTEM					
Ambient temperature, °C	+10 to +30	+10 to +30	+10 to +30	+10 to +30	+10 to +30
Refrigerant	R290	R600a	R600a	R600a	R600a
Refrigerant amount, gr	85	75	90	115	102
Climate class	3	4	4	4	4
Temperature range, °C	-18 to -24	-18 to -24	-18 to -24	-18 to -24	-18 to -24
Type of thermostat	Electronic	-	-	-	Mechanical
Static/Ventilated	Ventilated	Static	Static	Static	Static
ELECTRICAL					
Voltage, V	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50
Electronic display	Yes	-	-	-	-
Type of thermometer	-	Digital	Digital	Digital	Digital
Type of thermostat	-	Mechanical	Mechanical	Mechanical	Mechanical
ENERGY					
Energy consumption, kWh/24h	13.3	1.76	2.33	2.25	3.54
Energy consumption, kWh/year	4855	641	850	821	1292
Energy class	F	C	C	C	C
EEI	79	22.0	26.0	22.5	28.0
Input power, watt	680	-	-	-	-
FEATURES					
Light inside top	No	-	-	-	-
Light in door side	Yes	-	-	-	-
Cabinet color (All PS)	White	White	White	White	White
Inside color	White PS	Hammered aluminum	Hammered aluminum	Hammered aluminum	Hammered aluminum
Door color/type	Alum.frame glass	Sliding glass	Sliding glass	Sliding glass	Sliding glass
Lock	Yes	Yes	Yes	Yes	Yes
Wheels	2 in back	Castors	Castors	Castors	Castors
Defrost & removal of water	Automatic	Manual	Manual	Manual	Manual
Noise	50	50	50	50	50
Insulation, mm	50	-	-	-	-
Side change of door possible	Yes	-	-	-	-
Possible to build in	No	-	-	-	-
OPTION					
Graphics	-	Option	Option	Option	Option
Baskets - max. qty	-	2	3	4	5
SHIPPING					
Quantity in standard truck	57	-	126	60	54
Quantity in 20 ft container	27	48	-	-	-
Quantity in 40 ft HC container	57	141	105	79	71

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

STORAGE FREEZERS



HF271



HF396



HF506

STORAGE FREEZERS



DIMENSIONS	HF271	HF396	HF506
Outer dimensions, WxDxH, mm	960x600x850	1260x600x850	1560x600x850
Inner dimensions, WxDxH, mm	820x500x670	1160x500x670	1460x500x670
PACKAGING			
Dimensions WxDxH, mm	985x716x888	1302x716x888	1602x716x888
VOLUME			
Volume, Gross, L	256	373	476
Volume, Net, L	206	302	384
WEIGHT			
Weight, Gross, kg	50	57	64
Weight, Net, kg	48	55	60
BASKETS			
No. of baskets/shelves, pcs	1	2	2
Max. load, kg	-	-	-
Shelf material	-	-	-
TEMPERATURE			
Ambient temperature, °C	+10 to +35	+10 to +35	+10 to +35
Climate class	7	7	7
Temperature range, °C	-18 to -24	-18 to -24	-18 to -24
COOLING SYSTEM			
Refrigerant, type	R600a	R600a	R600a
Refrigerant amount, gr	84	90	106
Static/ventilated	Static	Static	Static
ELECTRICAL			
Voltage, V	220-240	220-240	220-240
Frequency, Hz	50	50	50
Voltage 110/60, V-Hz	N/A	Option	Option
Type of thermometer	Mechanical	Mechanical	Mechanical
Type of thermostat	Mechanical	Mechanical	Mechanical
Electronic display	-	-	-
ENERGY			
Energy consumption, kWh/24h	1,62	1,84	2,21
Energy consumption, kWh/year	591	672	807
Energy class	D	D	D
EEL	41,3	38,2	39,6
Input power, watt	-	-	-
FEATURES			
Light inside top	White	White	White
Light in door side	Hammered aluminum	Hammered aluminum	Hammered aluminum
Cabinet color (All PS)	White, lift up	White, lift up	White, lift up
Inside color	Stainless	Stainless	Stainless
Door color/type	-	-	-
Lock	Yes	Yes	Yes
Wheels/Casters/Feet	Feet	Feet	Feet
Defrost & removal of water	Manual	Manual	Manual
Noise	-	-	-
Insulation, mm	50	50	50
Side change of door possible	-	-	-
Possible to build in	-	-	-
OPTION			
Graphics	Option	Option	Option
Baskets - max. qty	3	6	7
SHIPPING			
Quantity in standard truck	141	90	81
Quantity in 20 ft container	-	-	-
Quantity in 40 ft HC container	105	79	70

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

STORAGE FREEZERS

WITH LIFT UP LID



SB 110
SB 220
SB 290
SB 370
SB 430
SB 500

SB 220 S
SB 290 S
SB 370 S
SB 430 S

STORAGE FREEZERS



DIMENSIONS	SB 110	SB 220	SB 290	SB 370	SB 430	SB 500
Outer dimensions, WxDxH, mm	550x600x850	890x600x860	1090x600x860	1320x600x860	1510x600x860	1700x600x860
Inner dimensions, WxDxH, mm	390x470x690	730x470x690	930x470x690	1160x470x690	1350x470x690	1540x470x690
PACKAGING						
Dimensions WxDxH, mm	590x660x890	950x710x880	1140x710x880	1370x710x880	1510x710x880	1700x710x880
VOLUME						
Volume, Gross, L	102	211	278	352	414	476
Volume, Net, L	99	209	275	349	411	472
WEIGHT						
Weight, Gross, kg	23	39	47	51	57	63
Weight, Net, kg	21	37	44	48	53	58
BASKETS						
No. of baskets, pcs	0	1	1	2	2	2
TEMPERATURE						
Ambient temperature, °C	+10 to +40	+10 to +40	+10 to +40	+10 to +40	+10 to +40	+10 to +40
Climate class	5	5	5	5	5	5
Temperature range, °C	-14 to -25	-14 to -25	-14 to -25	-14 to -25	-14 to -25	-14 to -25
COOLING SYSTEM						
Refrigerant, type	R600a	R600a	R600a	R600a	R600a	R600a
Refrigerant amount, gr	33	43	50	55	67	72
Static/ventilated	Static	Static	Static	Static	Static	Static
Freezing capacity, kg/24h	11	16	24	23	24	24
ELECTRICAL						
Voltage, V	220-240	220-240	220-240	220-240	220-240	220-240
Voltage 110/60, V-Hz	Option	Option	Option	Option	Option	Option
Frequency, Hz	50	50	50	50	50	50
Type of thermometer	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
ENERGY						
Energy consumption, kWh/24h	0,6	0,81	0,892	1,052	1,138	1,484
Energy consumption, kWh/year	219	296	326	384	415	542
Energy class	B	B	B	B	B	C
EEL	19,9	19,9	18,9	19,3	18,8	22,2
FEATURES						
Cabinet color	White	White	White	White	White	White
Inside material/color	White aluminum	White aluminum	White aluminum	White aluminum	White aluminum	White aluminum
Door or lid color/type	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up
Alternative lid	Stainless	Stainless	Stainless	Stainless	Stainless	Stainless
Lock	Yes	Yes	Yes	Yes	Yes	Yes
Castors/feet	Feet	Feet	Feet	Feet	Feet	Feet
Defrost & removal of water	Manual	Manual	Manual	Manual	Manual	Manual
Insulation, mm	55	65	65	65	65	65
OPTION						
Graphics	Option	Option	Option	Option	Option	Option
Baskets - max. qty	1	3	3+1*	4+1*	5+1*	6
SHIPPING						
Quantity in standard truck	216	112	96	75	69	60
Quantity in 20 ft container	88	42	40	28	25	18
Quantity in 40 ft HC container	216	112	96	75	69	60

*remove internal partition

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

STORAGE FREEZERS

WITH LIFT UP LID



SB 200



SB 300



SB 400

STORAGE FREEZERS




DIMENSIONS	SB 200	SB 300	SB 400
Outer dimensions, WxDxH, mm	920x600x850	1260x600x850	1560x600x850
Inner dimensions, WxDxH, mm	760x440x635	1100x440x635	1400x440x635
PACKAGING			
Dimensions WxDxH, mm	962x716x888	1302x716x888	1602x716x888
VOLUME			
Volume, Gross, L	198	296	383
Volume, Net, L	189	284	368
WEIGHT			
Weight, Gross, kg	48	60	68
Weight, Net, kg	45	57	65
BASKETS			
No. of baskets, pcs	2	4	5
TEMPERATURE			
Ambient temperature, °C	+10 to +35	+10 to +35	+10 to +30
Climate class	7	7	7
Temperature range, °C	-18 to -24	-18 to -24	-18 to -24
COOLING SYSTEM			
Refrigerant, type	R600a	R600a	R600a
Refrigerant amount, gr	55	78	95
Static/ventilated	Static	Static	Static
ELECTRICAL			
Voltage, V	220-240	220-240	220-240
Frequency, Hz	50	50	50
Type of thermometer	Mechanical	Mechanical	Mechanical
Type of thermostat	Mechanical	Mechanical	Mechanical
ENERGY			
Energy consumption, kWh/24h	0,68	0,99	1,17
Energy consumption, kWh/year	248	361	427
Energy class	B	C	C
EEL	18,7	21,8	23,0
FEATURES			
Cabinet color	White	White	White
Inside material/color	Hammered aluminum	Hammered aluminum	Hammered aluminum
Door or lid color/type	White, lift up	White, lift up	White, lift up
Alternative lid	Stainless	Stainless	Stainless
Lock	Yes	Yes	Yes
Castors/feet	Feet	Feet	Feet
Defrost & removal of water	Manual	Manual	Manual
Insulation, mm	80	80	80
OPTION			
Graphics	Option	Option	Option
Baskets - max. qty	3	5	6
SHIPPING			
Quantity in standard truck	94	60	54
Quantity in 20 ft container			
Quantity in 40 ft HC container	108	81	72

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

LOW TEMPERATURE

WITH LIFT UP LID



VT146



VT206



VT306



VT406



VT546

LOW TEMPERATURE




CONSTRUCTION	VT146	VT206	VT306	VT406	VT546
Outer Dimensions, WxDxH, mm	725x605x885	923x605x885	1265x605x885	1562x605x885	1664x605x885
Inner Dimensions, WxDxH, mm	560x440x635	760x440x635	1100x440x635	1400x440x635	1500x440x635
PACKAGING					
Dimensions WxDxH, mm	-	-	-	-	-
VOLUME					
Volume, Gross, L	140	198	296	384	495
Volume, Net, L	140	198	296	384	495
WEIGHT					
Weight, Gross, kg	55	63	77	83	108
Weight, Net, kg	51	58	71	77	92
BASKETS					
No. of baskets, pcs	1	1	1	1	3
TEMPERATURE					
Ambient temperature, °C	+10 to +30	+10 to +30	+10 to +30	+10 to +30	+10 to +30
Climate class	-	-	-	-	-
Temperature range, °C	-10 to -45	-10 to -45	-10 to -45	-10 to -45	-10 to -45
COOLING SYSTEM					
Refrigerant, type	R290	R290	R290	R290	R290
Refrigerant amount, gr	-	-	-	-	-
Static/ventilated	Static	Static	Static	Static	Static
ELECTRICAL					
Voltage, V	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50
Voltage 110/60, V-Hz	Option	Option	Option	Option	Option
Type of thermometer	Electronic	Electronic	Electronic	Electronic	Electronic
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic
Potential free contact for remote control	Yes	Yes	Yes	Yes	Yes
Porthole for sensor, ø12 mm	Yes	Yes	Yes	Yes	Yes
ENERGY					
Energy consumption, kWh/24h	1,865	3,14	3,74	4,09	4,16
Energy consumption, kWh/year	-	-	-	-	-
Energy class	not needed	not needed	not needed	not needed	not needed
EEL	not needed	not needed	not needed	not needed	not needed
Input power, watt	415	415	415	415	415
FEATURES					
Cabinet color	White	White	White	White	White
Inside material/color	White painted steel	White painted steel	White painted steel	White painted steel	White painted steel
Door or lid color/type	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up
Alternative lid	n/a	n/a	n/a	n/a	n/a
Lock	Yes	Yes	Yes	Yes	Yes
Castors/feet	Castors	Castors	Castors	Castors	Castors
Defrost & removal of water	Manual	Manual	Manual	Manual	Manual
Insulation, mm	80	80	80	80	80
OPTION					
Graphics	Option	Option	Option	Option	Option
Baskets - max. qty	-	-	-	-	-
SHIPPING					
Quantity in standard truck	216	168	120	96	96
Quantity in 20 ft container	-	-	-	-	-
Quantity in 40 ft HC container	94	78	54	42	38

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

LOW TEMPERATURE

WITH LIFT UP LID



VT75



VT147



VT207



VT307



VT407



VT547

LOW TEMPERATURE



CONSTRUCTION	VT75	VT147	VT207	VT307	VT407	VT547
Outer Dimensions, WxDxH, mm	555x555x870	725x605x885	923x605x885	1265x605x885	1562x605x885	1664x605x885
Inner Dimensions, WxDxH, mm	390x390x465	560x440x635	760x440x635	1100x440x635	1400x440x635	1500x440x635
PACKAGING						
Dimensions WxDxH, mm	-	-	-	-	-	-
VOLUME						
Volume, Gross, L	71	140	198	296	384	495
Volume, Net, L	71	140	198	296	384	495
WEIGHT						
Weight, Gross, kg	48	55	63	77	83	108
Weight, Net, kg	42	51	58	71	77	92
BASKETS						
No. of baskets, pcs	1	1	1	3	4	3
TEMPERATURE						
Ambient temperature, °C	+10 to +30	+10 to +30	+10 to +30	+10 to +30	+10 to +30	+10 to +30
Climate class	-	-	-	-	-	-
Temperature range, °C	-40 to -60	-40 to -60	-40 to -60	-40 to -60	-40 to -60	-40 to -60
COOLING SYSTEM						
Refrigerant, type	Mix of hydrocarbons	Mix of hydrocarbons	Mix of hydrocarbons	Mix of hydrocarbons	Mix of hydrocarbons	Mix of hydrocarbons
Refrigerant amount, gr	-	-	-	-	-	-
Static/ventilated	Static	Static	Static	Static	Static	Static
ELECTRICAL						
Voltage, V	220-240	220-240	220-240	220-240	220-240	220-240
Frequency, Hz	50	50	50	50	50	50
Voltage 110/60, V-Hz	Option	Option	Option	Option	Option	Option
Type of thermometer	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Type of thermostat	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Potential free contact for remote control	Yes	Yes	Yes	Yes	Yes	Yes
Porthole for sensor, ø12 mm	Yes	Yes	Yes	Yes	Yes	Yes
ENERGY						
Energy consumption, kWh/24h	2,2	3,71	3,12	5,56	7,08	5,78
Energy consumption, kWh/year	-	-	-	-	-	-
Energy class	not needed	not needed	not needed	not needed	not needed	not needed
EEl	not needed	not needed	not needed	not needed	not needed	not needed
Input power, watt	415	415	-	-	-	-
FEATURES						
Cabinet color	White	White	White	White	White	White
Inside material/color	White painted steel	White painted steel	White painted steel	White painted steel	White painted steel	White painted steel
Door or lid color/type	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up	White, lift up
Alternative lid	n/a	n/a	n/a	n/a	n/a	n/a
Lock	Yes	Yes	Yes	Yes	Yes	Yes
Castors/feet	Feet	Castors	Castors	Castors	Castors	Castors
Defrost & removal of water	Manual	Manual	Manual	Manual	Manual	Manual
Insulation, mm	80	80	80	80	80	80
OPTION						
Graphics	Option	Option	Option	Option	Option	Option
Baskets - max. qty	-	-	-	-	-	-
Variable speed compressor	Yes	Yes	Yes	Yes	Yes	Yes
SHIPPING						
Quantity in standard truck	288	216	168	120	96	96
Quantity in 20 ft container	-	-	-	-	-	-
Quantity in 40 ft HC container	114	94	78	54	42	38

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

QUALITY COOLING APPLIANCES



Vestfrost Solutions

Falkevej 12
6705 Esbjerg Ø
Denmark

+45 79 14 22 22

LML@vestfrostsolutions.com

BNE@vestfrostsolutions.com



Please see our website
for more information:

www.vestfrostsolutions.com

www.vestfrostsolutions.com/food/



www.linkedin.com/company/vestfrostsolutions



www.youtube.com/@vestfrostsolutionsDK

VESTFROST
SOLUTIONS