

VLS 096Ae RF AC

ICELINED REFRIGERATOR & ICEPACK FREEZER

This model has a built-in heating element ensuring that the appliance can maintain stable temperatures between +2°C to +8°C in all ambient temperatures, setting a new industry standard beyond the PQS requirement.

TrueBlue Series
**A NEW GENERATION
OF PRODUCTS**



+2°C
+8°C

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.

DIMENSIONS

Height, mm	940
Width, mm	1510
Depth, mm with handle	750
Gross weight, kg (incl. packaging)	190
Net weight, kg	150
Packed dimensions HxWxD, mm	1065x1560x785
Shipping volume m3	1,31

REFRIGERATOR SPECIFICATIONS

Gross volume, L	147
Net volume, L	110
Temperature range (+43°C AMB)	+2°C to +8°C
Hold-over time, hours (+43°C AMB)	93,04
Refrigerant	R600a
Freeze protection, grade	A
Climate class	T
WHO PQS code	TBA

FREEZER SPECIFICATIONS

Gross volume, L	50
Water pack storage capacity, L	28 x 0.6
Water pack freezing capacity, kg/24h	2.4
Temperature range (+43°C AMB)	-15° to -25°C
Refrigerant	R290 + R600a

FEATURES

Storage baskets, no	2
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
Charging port	USB A 5V
EMS level 3 as an option	YES
Industrial grade locking mechanism	YES
Automatic drainage system	YES

LOADING QUANTITIES

Qty. per 20' / 40' container	10 / 20
------------------------------	---------

VOLTAGE REGULATION RANGE

220-240V/50/60Hz	110-278V/50/60Hz
100-127V/50/60Hz	82-159V/50/60Hz
Integrated and extended voltage stabilizer as standard in line with PQS E007/VS01-VP.6	

Find our EMS datasheet [here](#).

This model comes equipped with our fully integrated remote equipment monitoring system (EMS) as standard. An upgrade to EMS level 3 is available as an option for enhanced monitoring capabilities.

Updated 09/2026