

PRODUCT

VLS 076 RF SDD SOLAR DIRECT DRIVEN COMBI

The appliance can maintain stable temperatures between +2°C to +8°C in all ambient temperatures. The included solar panel kit of 4 x 180W, is connected plug & play, directly to the appliance. The VLS SDD has an integrated safety thermostat, and junction box to safeguard and provide easy access to electrical components. The appliance comes with industrial locking mechanism, adjustable legs and storage baskets. All VLS SDD RF models have been tested and PQS approved according to the newest performance standards. Our fully integrated remote equipment monitoring system (EMS) can be added as an option for this model.



REFRIGERATOR SPECIFICATIONS

Gross volume, L	111
Net volume, L	61
Temperature range (43C AMB)	+2 to +8C
Autonomy, hours	72
Refrigerant	R600a
Freeze protection, grade	A
Climae class	T
WHO PQS code	E003/119

FEATURES

Storage baskets, no	2
Temperature control	Automatic
Lock + keys	YES
Junction box	YES
Adjustable legs	YES, 10cm
Safety thermostat	YES
Industrial grade locking mechanism	YES

FREEZER SPECIFICATIONS


Gross volume, L	34
Water pack storage capacity, L	29 x 0.6
Water pack freezing capacity, L	1.8
Temperature range (43C AMB)	-18 to -28C
Refrigerant	R290 + R600a

DIMENSIONS

Height, mm	950
Width, mm	1110
Depth, mm with handle	700
Gross weight, kg	162
Net weight, kg	125

LOADING QUANTITIES

Qty. per 20' / 40' container	10/30
------------------------------	-------



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



COLD CHAIN SOLUTIONS

VESTFROST
SOLUTIONS

A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostsolutions.com