

E003:	Refrigerators and freezers	
PQS code:	E003/111	
Type of appliance:	Icelined refrigerator	
Manufacturer's reference:	VLS 354A AC	
Manufactured in:	Denmark	
Company:	Vestfrost Solutions	
Address:	A/S Vestfrost Falkevej 12 DK-6705 Esbjerg Ø Denmark	
Telephone:	+45 7914 2555; +45 7914 2248	
Email:	clc@vestfrostsolutions.com; bjn@vestfrostsolutions.com	
Web address:	http://vestfrostsolutions.com/	

## **Specifications**

Climate zone:	Hot	Min rated ambient temp:	+5°C
Refrigerant:	R600a	Energy source:	Electric Mains 220-240V 50/60Hz or Electric Mains 115/60Hz optional
Appliance tested at:	+43°C	Ext dimensions (HxLxD)	85 x 113 x 70 cm
Performance at:	+43°C	Fuel and cycle type:	Electric - compression
REFRIGERATOR		FREEZER	Freeze protection: Grade A
Vaccine storage capacity: (Litres)	127 L in baskets		
Gross volume (Litres):	209 L	Gross volume:	N/A
Holdover time (hours):	54.7 hours	Waterpack freezing capacity:	N/A
Energy consumption, stable running (kWh/24 hours):	0.62kWh/24h	Waterpack storage capacity:	N/A
Energy consumption, cool down test (kWh/24 hours):	0.64 kWh/24h	Energy consumption during freezing:	N/A

Current PQS status:	pre-qualified: 02 Oct 2019	Validity until:	: April, 2023		
Verification report:	12057110OMKS-003a amended	Verification laboratory:			
Quality standard:	- ISO 9001:2008 - ISO 13485 - ISO 14001 - DS/OHSAS 18001:2008 -	Specification ref.			
Price					
Price year	2016	Incoterms	FCA		
Shipping volume:	0.85 m3	Shipping weight:	110 kg		
	1 No Thermostat - Part No.7095348 1 No Starting device (103N0021) Part No.A921115 1 No Thermometer, solar, Part No.7020287-03 Other parts are available as spares on request.				
Spare parts (ref, price):	Included in the UNICEF Supply Division spare parts kit: 1 No Compressor (NLE 9KTK, Complete) - Part No.8-036038255				
Accessories:	4 x Vaccine storage top basket; 3 x Vaccine bottom basket; 1 x Bottom grating; 1 x Voltage stabilizer; 1 x 30 day electronic temperature logger; 1 x Holder for temperature logger; Self-regulating temperature control; Electronic temperature reading; 2 x Keys; Instruction manual in 6 UN languages; Technical manual in 6 UN languages; Plywood packing/crate				
Comments:	<ul> <li>Equipped with unique QR code that can be used with Vestfrost Solutions Unit tracker APP, containing various installation/service features.</li> <li>Electrical components positioned in corrosion free metal junction box, protecting for water, dust intrusion, and eases service/maintenance.</li> <li>For easy customization to local standard plug, supplied with appliance power in-let + appliance power plug/cable.</li> <li>Supplied with adjustable legs, elevating appliance to protect against water/rubbish etc.</li> <li>VLS 354A AC imodel is supplied with internal voltage stabilizer for extended input range, incl. high, low, spike and surge protection in line with E007/VS01-VP.5</li> <li>For 220-240V/50/60Hz, input voltage regulation range 110-278V/50/60Hz</li> <li>For 100-127V/50/60Hz, input voltage regulation range 82-159V/50/60Hz</li> <li>As an option the appliance can be supplied with Vestfrost in-built RTMD; with following features: 1: 5" touch display 2: 3X internal temp. sensors 3: ambient temp. 4: compressor sensor 5: humidity sensor 6: lid opening alarm 7: GPS coordinates via Google maps 8: 1X USB 5V solar harvesting port. All data collected/logged is automatic via GPRS uploaded to Vestfrost RTMD performance data-portal, and/or can be accessed onsite from the touch screen menu.</li> </ul>				

Note: If Current PQS status is 'Suspended' or 'Withdrawn', this product is NOT to be purchased.